

## W 18 L BL 9-115 (602373850) Cordless angle grinder 18V; Cardboard box

Order no. 602373850  
EAN 4061792230385



Product may differ from Image



- Service-free Brushless motor with highest efficiency and maximum handiness
- Slim design for low-fatigue working
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                  |
|-----------------------------|------------------|
| Battery voltage             | 18 V             |
| Disc-Ø                      | 115 mm / 4 1/2 " |
| Max. cutting depth          | 29 mm / 1.142 "  |
| No-load speed               | 10000 rpm        |
| Spindle thread              | M 14             |
| Handle circumference        | 183 mm / 7.205 " |
| Weight without battery pack | 1.5 kg           |
| Weight with battery pack    | 2.2 kg           |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 5 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 86 dB(A) |
| Sound power level (LwA)      | 97 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Guard  
Side handle  
Flat-pin spanners  
without battery pack, without charger  
Inner support flange  
Nut with two holes