

SSD 18 LTX 200 BL (602396720) Cordless impact driver 18V 2x4Ah LiHD; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145

Order no. 602396720 EAN 4061792191891



Product may differ from Image







- Compact cordless impact driver with 1/4" hexagon recess and 200 Nm, versatile application
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



| Technical data | |
|------------------------------|-------------------------------|
| Characteristics | |
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 4 Ah |
| Max. screw size | M16 |
| Max. no-load speed | 0 - 2900 rpm |
| Maximum impact rate | 4000 bpm |
| Maximum torque | 200 Nm / 150 ft. lbs |
| Speed/torque levels | 12 |
| Bit retainer | Hexagon recess 1/4" (6.35 mm) |
| Weight with battery pack | 1.4 kg / 3.1 lbs |
| Vibration | |
| Impact screwdriving | 9 m/s² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Belt Hook

metaBOX 145

2 LiHD Battery packs (18 V/4.0 Ah)

Charger ASC 55 "AIR COOLED"

www.metabo.com 2/2