

## SSD 18 LTX 200 BL (602396840) Cordless impact driver 18V; metaBOX 145

Order no. 602396840  
EAN 4007430330147



Product may differ from Image



- Compact cordless impact driver with 1/4" hexagon recess and 200 Nm, versatile application
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                               |
|-----------------------------|-------------------------------|
| Battery voltage             | 18 V                          |
| Max. screw size             | M16                           |
| Max. no-load speed          | 2900 rpm                      |
| Maximum impact rate         | 4000 bpm                      |
| Maximum torque              | 200 Nm / 150 ft. lbs          |
| Speed/torque levels         | 12                            |
| Bit retainer                | Hexagon recess 1/4" (6.35 mm) |
| Weight without battery pack | 0.94 kg / 2.1 lbs             |
| Weight with battery pack    | 1.3 kg / 2.9 lbs              |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Impact screwdriving          | 9 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 94 dB(A)  |
| Sound power level (LwA)      | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Belt Hook  
 metaBOX 145  
 without battery pack, without charger