

## BS 18 LTX-3 BL Q I Metal (603180850) Cordless drill / screwdriver 18V; Cardboard box

Order no. 603180850

EAN 4061792211643



Product may differ from Image



- Brushless 3-speed drill/screwdriver with maximum power: ideal for demanding metal applications
- Extremely powerful chuck with re-tensioning function against slipping of the bit and high degree of concentricity
- Third speed setting with high torque (max. 4,000/min) for extended range of application and even faster drilling progress, especially in metal
- Metabo QuickPlus System: quick change of bit retainer and bits, for flexible working with maximum load
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

Battery voltage	18 V
Maximum torque, soft	65 Nm / 575.3 in-lbs
Maximum torque, hard	130 Nm / 1150.6 in-lbs
Adjustable torque	1 - 18 Nm // 8.9 - 159.3 in-lbs
Drill Ø steel	16 mm / 5/8 "
Drill-Ø soft wood	68 mm / 2.68 "
No-load speeds	0 - 450 / 0 - 2000 / 0 - 4000 rpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1.69 "
Weight without battery pack	2 kg / 4.4 lbs
Weight with battery pack	3 kg / 6.6 lbs

### Vibration

Drilling in metal	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	75 dB(A)
Sound power level (LwA)	85 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Futuro Top quick-change chuck "QuickPlus"  
without battery pack, without charger  
Side handle  
C-wrench