

## RF 14-115 (603823810) Renovation Milling Machine (220-240 V / 50 - 60 Hz); Plastic Carry Case; with Cutter Head (pointed)

Order no. 603823810  
EAN 4007430265593



Product may differ from Image



- For effective removal of plaster, adhesive residues, soft screed and old paint from walls, ceilings and floors
- Triple reduction high-performance gearing for maximum torque and high output
- Fast work progress thanks to large milling diameter
- Cutting depth can be adjusted easily and without the need for tools
- Robust protective cover made from die-cast aluminium with spring-mounted brush rim for low-dust working
- Support ring for easy guidance of the machine and to provide a stop for working near edges
- Front handle for safe and uniform guidance when milling, adjustable without tools
- Metabo Marathon motor with patented dust protection for long service life
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Overload protection: protects the motor from overheating
- Auto-stop carbon brushes to protect the motor
- Aluminium flange for long service life when using heavy accessories, e.g. diamond cup wheels

**Technical data****Characteristics**

Working width	115 mm
Cutting depth	3 - 6 mm // 1/8 - 1/4 "
Torque	9 Nm / 80 in-lbs Nm
No-load speed	800 - 2800 rpm
Rated input power	1450 W
Output power	780 W
Revolutions at rated load	2800 rpm
Spindle thread	M 14
Weight (without power cable)	4.3 kg / 9.5 lbs
Cable length	4 m / 13 ft

**Vibration**

Surface grinding	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

**Noise emission**

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

**Scope of delivery**

Bow-type handle  
Flat-pin spanner  
Hexagonal wrench  
Plastic carry case  
Cutter head pointed (complete)