

## RFEV 19-125 RT (603826760) Renovation milling machine (110-120 V / 50 - 60 Hz); Plastic Carry Case; with milling head pointed

Order no. 603826760  
EAN 4007430313744



Product may differ from Image



- For effective removal of plaster, adhesive residues, soft screed and old paint from walls, ceilings and floors
- Maximum productivity thanks to top 1,900 Watt with low weight
- Double reduction high-performance gearing for maximum torque and high output
- Fast work progress thanks to large milling diameter
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Cutting depth can be adjusted easily and without the need for tools
- Robust protective cover made from die-cast aluminium with spring-mounted brush rim for low-dust working
- Front handle for safe and uniform guidance when milling, adjustable without tools
- Can be used as renovation grinder on smaller areas when using a diamond cup wheel
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Connection for dust extraction Ø 35/41 mm

## Technical data

### Characteristics

|                              |                       |
|------------------------------|-----------------------|
| Working width                | 125 mm                |
| Cutting depth                | 0 - 6 mm // 0 - 1/4 " |
| Torque                       | 16.8 Nm               |
| No-load speed                | 750 - 3100 rpm        |
| Rated input power            | 1900 W                |
| Output power                 | 1240 W                |
| Speed at rated load          | 2800 rpm              |
| Spindle thread               | M 14                  |
| Weight (without power cable) | 3.8 kg / 8.4 lbs      |
| Cable length                 | 2.5 m / 8 ft          |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Surface grinding             | 3.38 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LwA)      | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Bow-type handle  
 Suction Adapter  
 Flat-pin spanners  
 Hexagonal wrench  
 Plastic carry case  
 Milling head pointed  
 Replacement Brush Rim