

## DP 18-5 SA (604111000) Drainage Pump (220-240 V / 50 Hz); Cardboard box

Order no. 604111000  
EAN 4007430221537



Product may differ from Image



- For effective pumping of large quantities of dirty water, rain water, ground water and water on construction sites
- Mechanical seal for protection of the pump if the water is particularly dense or contains large particles
- Self-cleaning Vortex-impeller to minimise blockages
- Designed for continuous mode with S1 motor operating mode
- Overload protection: protects the motor from overheating
- Float switch for automatic mode
- Suitable for mobile and stationary use thanks to ergonomic handles and stability

**Technical data****Characteristics**

Rated input power	900 W
Maximum delivery rate	18000 l/h / 4755 gal/h
Maximum delivery height	9.4 m / 30 ft
Maximum pressure	0.94 bar / 13.63 psi
Maximum immersion depth	7 m / 23 ft
Discharge port	1 1/2" female thread
Pump housing	Aluminium
Protection type IP	IP 68
Maximum particle size up to	5 mm / 3/16 "
Number of impellers	1
Dimensions	169 x 169 x 416 mm // 6 21/32 x 6 21/32 x 16 3/8 "
Weight	10 kg / 22 lbs
Cable length	10 m / 33 ft

**Scope of delivery**

Float switch