

## WE 22-230 MVT (606464580) Angle grinder

(220-240 V / 50 - 60 Hz); Plastic Carry Case; with rotating main handle, deadman switch

Order no. 606464580 EAN 4007430268471



Product may differ from Image











- Metabo Marathon motor with patented dust protection for long service life
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Deadman's switch for high user protection
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

www.metabo.com 1/2



| Technical data               |                      |
|------------------------------|----------------------|
| Characteristics              |                      |
| Disc-Ø                       | 230 mm // 9 "        |
| Rated input power            | 2200 W               |
| Output power                 | 1500 W               |
| No-load speed                | 6600 rpm             |
| Speed at rated load          | 4600 rpm             |
| Torque                       | 14 Nm / 124 in-lbs   |
| Spindle thread               | M 14                 |
| Handle circumference         | 144 mm / 5.669 "     |
| Weight (without power cable) | 5.8 kg / 12.8 lbs    |
| Cable length                 | 4 m / 13 ft          |
| Vibration                    |                      |
| Surface grinding             | 6.2 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Noise emission               |                      |
| Sound pressure level         | 94 dB(A)             |
| Sound power level (LwA)      | 105 dB(A)            |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Flat-pin spanner

Plastic carry case

Inner support flange

Nut with two holes

www.metabo.com 2/2