

## W 24-180 MVT (606466260) Angle grinder

(220-240 V / 50 - 60 Hz); Cardboard box; with rotating main handle, deadman switch

Order no. 606466260 EAN 4007430334138



Product may differ from Image







- Metabo Marathon motor with patented dust protection for long service life
- Deadman's switch for high user protection
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	180 mm // 7 "
Rated input power	2400 W
Output power	1600 W
No-load speed	8450 rpm
Speed at rated load	5800 rpm
Torque	14 Nm / 124 in-lbs
Spindle thread	M 14
Handle circumference	144 mm / 5.669 "
Weight (without power cable)	5.7 kg / 12.6 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6.1 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Flat-pin spanner

Inner support flange

Nut with two holes

www.metabo.com 2/2