

## W 24-230 MVT (606467000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with rotating main handle

Order no. 606467000 EAN 4007430268143



Product may differ from Image

- Metabo Marathon motor with patented dust protection for long service life
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

## Technical data

## Characteristics

| Disc-Ø                              | 230 mm // 9 "         |
|-------------------------------------|-----------------------|
| Rated input power                   | 2400 W                |
| Output power                        | 1600 W                |
| No-load speed                       | 6600 rpm              |
| Speed at rated load                 | 4600 rpm              |
| Torque                              | 17 Nm / 150 in-lbs    |
| Spindle thread                      | M 14                  |
| Handle circumference                | 144 mm / 5.669 "      |
| Weight (without power cable)        | 5.8 kg / 12.8 lbs     |
| Cable length                        | 4 m / 13 ft           |
| Vibration                           |                       |
| Surface grinding                    | 6.2 m/s <sup>2</sup>  |
| Uncertainty of measurement K        | 1.5 m/s <sup>2</sup>  |
| Grinding with sandpaper             | 2.5 m/s <sup>2</sup>  |
| Uncertainty of measurement K        | 1.5 m/s <sup>2</sup>  |
|                                     |                       |
| Noise emission                      |                       |
| Noise emission Sound pressure level | 94 dB(A)              |
|                                     | 94 dB(A)<br>105 dB(A) |

## Scope of delivery

Guard Metabo VibraTech (MVT) side handle Flat-pin spanner Inner support flange Nut with two holes