# W 26-180 MVT (606473260) Angle grinder

**(220-240 V / 50 - 60 Hz); Cardboard box; with rotating main handle, deadman switch**

Order no. 606473260
EAN 4007430268280




Product may differ from Image

- Metabo Marathon motor with patented dust protection for long service life
- Deadman's switch for high user protection
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user’s health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

| | |
|---|---|
| Disc-Ø | 180 mm // 7 " |
| Rated input power | 2600 W |
| Output power | 1800 W |
| No-load speed | 8450 rpm |
| Speed at rated load | 6000 rpm |
| Torque | 17 Nm / 150 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 144 mm / 5.669 " |
| Weight (without power cable) | 6.2 kg / 13.7 lbs |
| Cable length | 4 m / 13 ft |

### Vibration

| | |
|---|---|
| Surface grinding | 5.8 m/s² |
| Uncertainty of measurement K | 1.5 m/s² |
| Grinding with sandpaper | 2.5 m/s² |
| Uncertainty of measurement K | 1.5 m/s² |

### Noise emission

| | |
|---|---|
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

## Scope of delivery

Guard
Metabo VibraTech (MVT) side handle
Flat-pin spanner
Inner support flange
Nut with two holes