

## HS 8865 (608865000) Hedge trimmer (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 608865000  
EAN 4007430180872



Product may differ from Image



- Double reduction gearing for particularly high cutting performance
- Patented Metabo handle system with additional switch for up to 50% more reach and range
- Low weight avoids fatigue when working
- Patented mechanical quick blade stop (in 0.05 seconds) for improved safety
- Blades with special geometry generate less wear and thus deliver 200% longer service life
- Clean cut thanks to diamond-ground blade teeth on both sides at a 30° angle
- Lower safety blade for high safety at work
- Metabo S-automatic safety clutch: Protects blades and gears when debris or large branches stop the blades
- Fatigue-proof operation due to ergonomic full grip bow-type handle design and optimum centre of gravity position
- Very quiet running due to shear blades running in opposite direction
- User-friendly guidance of machine exhaust in all working situations
- Particularly easy to service thanks to carbon brush and cable replacement cover
- Cable strain relief prevents the unintentional disconnection of the plug-in connection
- Trigger guard with twig feed protects user and gear from kickbacks

## Technical data

### Characteristics

|                              |                  |
|------------------------------|------------------|
| Max. cutting thickness       | 26 mm / 1 "      |
| Cutting length               | 65 cm / 26 "     |
| Blade clearance              | 34 mm / 1 3/8 "  |
| Number of strokes (No Load)  | 2900 spm         |
| Rated input power            | 660 W            |
| Weight (without power cable) | 4.2 kg / 9.3 lbs |
| Cable length                 | 0.3 m / 1 ft     |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Idle                         | 3.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 84 dB(A) |
| Sound power level (LwA)      | 95 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Trigger guard

Container