

SRE 4350 TurboTec (611350000) Orbital sander (220-240 V / 50 Hz); Cardboard box

Order no. 611350000 EAN 4007430214218



Product may differ from Image

- Excellent sanding finish without scoring marks and grooves, for a professional surface finish
- Oscillating system with double-row angular ball bearing for extremely smooth running and minimum vibration
- Robust clamping system for sanding paper with or without hook and loop fastener, as well as sanding medium up to 10 mm in thickness
- Ball bearing with multiple sealings and tear-proof rubber sleeve protects the machine against aggressive dust
- Side handle with vibration damping for a comfortable grip in any work position
- TurboBoost: allows additional power reserves to be employed for maximum removal
- Vario (V)-Electronics for working at customised orbital frequencies to suit various application materials
- Sanding plate with additional lateral extraction channels for cleaner working
- Dust cartridge with filter for working without connecting to a vacuum cleaner
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

www.metabo.com 1/2



| Technical data | | |
|--------------------------------|-------------------------|--|
| Characteristics | | |
| Base plate | 92 x 184 mm (1/3 sheet) | |
| Rated input power | 350 W | |
| No-load speed | 4200 - 11000 rpm | |
| Orbital frequency with no load | 8400 - 22000 opm | |
| Orbit diameter | 2.2 mm / 3/32 " | |
| Weight (without power cable) | 2.4 kg / 5.3 lbs | |
| Cable length | 4 m / 13 ft | |
| Vibration | | |
| Surface grinding | 3.3 m/s ² | |
| Uncertainty of measurement K | 1.5 m/s ² | |
| Noise emission | | |
| Sound pressure level | 79 dB(A) | |
| Sound power level (LwA) | 90 dB(A) | |
| Uncertainty of measurement K | 3 dB(A) | |

Scope of delivery

Hook and loop grinding plate removable side handle Textile dust bags

www.metabo.com 2 / 2