

TS 36-18 LTX BL 254 (613025810) Cordless table saw

18V 4x8Ah LiHD; Charger ASC 145 Duo (220-240 V / 50 - 60 Hz); Cardboard box; with stand and trolley function

Order no. 613025810

EAN 4007430334930



Product may differ from Image



- Extremely light cordless table saw with trolley function for maximum mobility
- Powerful Brushless motor for powerful sawing like with a mains-powered tool
- 100% compatibility with the 18 Volt class: powerful 36 Volt operation with two 18 Volt battery packs from Metabo
- Integrated extraction with dust cyclone for low-dust working without vacuum cleaner
- Quick change between sawing at ground-level or when standing up thanks to integrated, folding stand
- Precise saw blade inclination via gear guide
- Precisely adjustable parallel guide / rip fence with double clamping and quick fastening
- Extra-large support surface thanks to table width extension and table length extension
- Soft start and overload protection for long service life of motor and drive
- Safe working thanks to restart protection and motor brake for quick stop of the saw blade
- Splitting wedge can be lowered without tools for hidden cuts and transport
- MetaLoc case and attachments can be fixed at the housing for compact transport and storage
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

Type of battery pack	LiHD
Battery voltage	18 V
Battery pack capacity	4 x 8 Ah
Max. support surface	970 x 995 mm
Working height	850 / 355 mm
Cutting height	0 - 87 mm
Maximum cutting height 90/45°	87 / 50 mm
Maximum cutting width at rip fence	630 mm
Maximum material width at mitre fence	200 mm
No-load speed	5000 rpm
Max. cutting speed	66 m/s
Saw blade	254 x 30 mm
Saw blade swivel range	-1.5 - 46.5 °
Weight without battery pack	33 kg / 72.8 lbs
Weight with battery pack	35 kg / 77.2 lbs

Noise emission

Sound pressure level	90 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (40 teeth)

Rip Fence

Mitre Fence

Table Length Extension

Table Width Extension

Push stick

Dust cycles

Textile dust bag

4 LiHD battery packs (18 V/8.0 Ah)

2 Quick Chargers ASC Ultra "AIR COOLED"

Fixation strap for MetaLoc

Stand

MetaLoc case

Rubber tyres