

WPB 18 LT BL 11-125 Quick (613059520) Cordless angle grinder 18V 2x5.5Ah LiHD; Charger ASC 145; metaBOX 165 L; with brake, quick-locking nut

Order no. 613059520
EAN 4061792229983



Product may differ from Image



- Brushless cordless angle grinder of the new generation: as powerful as a 1,100 Watt mains-powered tool thanks to 40% more power
- Service-free Brushless motor with highest efficiency and maximum handiness
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Fast brake system for highest user safety stops the disc within a matter of seconds after switching off
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety
- Restart protection: prevents unintentional start-up after battery pack change
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-----------------------------|------------------|
| Type of battery pack | LiHD |
| Battery pack capacity | 2 x 5.5 Ah |
| Battery voltage | 18 V |
| Disc-Ø | 125 mm / 5 " |
| Max. cutting depth | 33 mm / 1.299 " |
| No-load speed | 10000 rpm |
| Spindle thread | 5/8" - 11 UNC |
| Handle circumference | 160 mm / 6.299 " |
| Weight without battery pack | 1.8 kg |
| Weight with battery pack | 2.8 kg |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 81 dB(A) |
| Sound power level (LwA) | 92 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Clip for cut-off guard
 M-Quick flange nut
 Side handle
 Dust Protection Filter
 2 LiHD battery packs (18 V/5.5 Ah)
 Quick charger ASC 145 "AIR COOLED"
 metaBOX 165 L
 Guard
 Inner support flange