

## WPF 18 LTX 125 (613070860) Cordless flat-head angle grinder 18V; Cardboard box

Order no. 613070860  
EAN 4007430244680



Product may differ from Image



- Cordless angle grinder with extremely low gear head for working in acute angles down to 43°
- Compact design for quick removal of welding slag, rust or paint in tight places e.g. frame constructions
- Low-fatigue working even on weld seams in difficult to access places thanks to slim handle
- Paddle switch with deadmans function: safe to operate due to an ergonomically integrated non-slip switch
- Robust motor for long service life
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better working in hard to reach places
- Detachable dust filter protects motor from coarse particles
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                |
|-----------------------------|----------------|
| Type of battery pack        | Li-Power       |
| Battery voltage             | 18 V           |
| Minimum accessible angle    | 43 °           |
| Disc-Ø                      | 125 mm / 5 "   |
| No-load speed               | 8000 rpm       |
| Spindle thread              | 5/8" - 11 UNC  |
| Weight without battery pack | 2 kg / 4.4 lbs |
| Weight with battery pack    | 2.7 kg / 6 lbs |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 4.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 83 dB(A) |
| Sound power level (LwA)      | 94 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

5 Flap discs Flexiamant Super Convex (125mm; P60)  
 Nut with two holes  
 Side handle  
 Dust Protection Filter  
 Flat-pin spanner  
 without battery pack, without charger  
 Guard  
 Inner support flange