

## WEVF 10-125 Quick Inox (613080420) Flat-head angle grinder (110-120 V / 60 Hz); Cardboard box

Order no. 613080420

EAN 4007430285126



Product may differ from image



- The most easy-to-handle flat-head angle grinder with speed regulation for perfect processing of stainless steel e.g. railings and hand rails
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Longer service life, more power: the Metabo Longlife-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Thumbwheel controlled Vario-Constamatic (VC)-Full wave electronics ideal for working on materials requiring customised speeds, and at speeds which remain almost constant under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

|                              |                    |
|------------------------------|--------------------|
| Minimum accessible angle     | 43 °               |
| Disc-Ø                       | 125 mm / 5 "       |
| Rated input power            | 1000 W             |
| Output power                 | 550 W              |
| No-load speed                | 2000 - 7600 rpm    |
| Speed at rated load          | 6300 rpm           |
| Torque                       | 3.5 Nm / 31 in-lbs |
| Spindle thread               | 5/8" - 11 UNC      |
| Weight (without power cable) | 2.3 kg / 5.1 lbs   |
| Cable length                 | 2.5 m / 8 ft       |
| Handle circumference         | 193 mm / 7.594 "   |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 4.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 91 dB(A)  |
| Sound power level (LwA)      | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Guard  
 Side handle  
 1 Flap disc Flexiamant Super Convex (125mm; P60)  
 Inner support flange  
 Quick-locking nut