

KS 305 M (619003000) Mitre saw (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 619003000 EAN 4007430299727



Product may differ from Image







- Highest precision from direct saw head mount.
- Compact light weight, suitable also for one-handed transport
- Robust die-cast aluminium design for the highest demands
- Easy transport thanks to ergonomically-designed handles and saw head lock
- Effective dust extraction via integrated dust scoop
- Fast and precise setting of common angles using stop points
- Laser for exact display of the cutting line (mains powered, no batteries required)
- Extendable table width extensions, also removable to put underneath extremely long work pieces
- Bright LED work light for illumination of the cutting line (mains powered, no batteries required)
- Sliding high rear fence profiles for safe sawing
- Quick-action clamp for secure fixing of the work piece from the top or front
- Saw head can be inclined to the left, with additional angle range for undercuts
- All scales and operating elements are visible from the working position and can be operated intuitively
- Easy saw blade change by means of spindle lock: No dismantling of the pendulum guard required

www.metabo.com 1/2



| Technical data | |
|----------------------------------|--|
| Characteristics | |
| Dimensions | 600 x 600 x 600 mm // 23 5/8 x 23 5/8 x 23 5/8 " |
| Support surface | 340 x 775 mm // 13 3/8 x 30 1/2 " mm |
| Maximum cutting width 90°/45° | 200 / 140 mm // 7 7/8 / 5 1/2 " |
| Maximum cutting depth at 90°/45° | 102 / 60 mm // 4 / 2 3/8 " |
| Cutting capacity 90°/90° | 200 x 80 mm // 7 7/8 x 3 5/32 " |
| Cutting capacity 45°/45° | 130 x 45 mm // 5 1/8 x 1 25/32 " |
| Turntable setting left/right | 52 / 52 ° |
| Saw blade tilt left/right | 47 / 2 ° |
| Saw blade | 305 x 30 mm // 12 x 1 3/16 " |
| Rated input power S1 100% | 1600 W |
| Rated input power S6 20% | 2000 W |
| No-load speed | 3700 rpm |
| Speed at rated load | 2600 rpm |
| Cutting speed | 60 m/s // 197 ft/s |
| Weight | 17 kg / 37.5 lbs |
| Cable length | 2 m / 6.5 ft |
| Noise emission | |
| Sound pressure level | 97 dB(A) |
| Sound power level (LwA) | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Carbide saw blade (56 teeth)

Supplementary Fence

Material clamp

Tool for saw blade change

Cable winder

Chip Collection Bag

2 Table length extensions

Length Guide

www.metabo.com 2 / 2