

## Set KS 66 FS (691135000) Circular saw (220-240 V / 50 - 60 Hz); Cardboard box; with guide rail FS 160

Order no. 691135000 EAN 4061792173255



Product may differ from Image



- Robust circular saw, can be used directly on guide rails from Metabo and also Mafell, Bosch, Festool, Makita, HiKOKI, Hilti and other manufacturers
- Fast, precise cross cuts thanks to easy coupling with a Metabo cross cutting rail
- Light guide plate made from die cast aluminium
- Grip area with non-slip soft-grip surface
- Clearly visible cutting indicator for precise sawing after initial cut
- 0° position re-adjustable for highest cutting precision
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Sawdust ejection nozzle for any working position can be rotated and locked individually

www.metabo.com 1 / 2



| Technical data                     |                                 |
|------------------------------------|---------------------------------|
| Characteristics                    |                                 |
| Rated input power                  | 1500 W                          |
| Output power                       | 840 W                           |
| Maximum cutting depth at 90°       | 66 mm / 2 5/8 "                 |
| Maximum cutting depth at 45°       | 47 mm / 1 7/8 "                 |
| Max. cutting depth with guide rail | 61 mm / 2 13/32 "               |
| Saw blade Ø x bore                 | 190 x 30 mm // 7 1/2 x 1 3/16 " |
| Swivel range from / to:            | 0 / + 47 °                      |
| No-load speed                      | 5000 rpm                        |
| Speed at rated load                | 3800 rpm                        |
| Max. cutting speed                 | 50 m/s                          |
| Weight (without power cable)       | 4.9 kg / 10.8 lbs               |
| Cable length                       | 4 m / 13 ft                     |
| Noise emission                     |                                 |
| Sound pressure level               | 95 dB(A)                        |
| Sound power level (LwA)            | 106 dB(A)                       |
| Uncertainty of measurement K       | 3 dB(A)                         |

## Scope of delivery

Guide rail FS 160 (160 cm)

Hexagonal wrench

Carbide circular saw blade (24 teeth)

Parallel guide

www.metabo.com 2 / 2