

## WEQ 1400-125 (600347190) Angle grinder Cardboard box; with quick-locking nut

Order no. 600347190  
EAN 4061792173378



Product may differ from Image



- Robust, universal and economical: powerful angle grinder for any application
- Powerful motor with good overload capacity
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection for long service life
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting

**Technical data****Characteristics**

|                              |           |
|------------------------------|-----------|
| Disc-Ø                       | 125 mm    |
| Rated input power            | 1400 W    |
| Output power                 | 780 W     |
| No-load speed                | 11500 rpm |
| Speed at rated load          | 10500 rpm |
| Torque                       | 3.3 Nm    |
| Spindle thread               | M 14      |
| Handle circumference         | 194 mm    |
| Weight (without power cable) | 2.2 kg    |
| Cable length                 | 4 m       |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 7.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 87 dB(A) |
| Sound power level (LwA)      | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

**Scope of delivery**

Guard  
Inner support flange  
M-Quick flange nut  
Side handle