

## WEV 15-125 Quick (600468190) Angle grinder Cardboard box; with speed control, quick-locking nut

Order no. 600468190 EAN 4007430245571



Product may differ from Image















- Highest service life for extreme applications: robust, powerful angle grinder with speed control and greatest power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	125 mm
Rated input power	1550 W
Output power	940 W
No-load speed	2800 - 11000 rpm
Speed at rated load	11000 rpm
Torque	3.5 Nm
Spindle thread	M 14
Handle circumference	206 mm
Weight (without power cable)	2.5 kg
Cable length	4 m
Vibration	
Surface grinding	6 m/s²
Uncertainty of measurement K	1.5 m/s²
Grinding with sandpaper	3.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2