

## GB 18 LTX BL Q I (602362850) Cordless tapper 18V; Cardboard box

Order no. 602362850  
EAN 4061792188198



Product may differ from Image



- High-grade, powerful drill for the most demanding applications with unique, patented thread-tapping function.
- Quick and interruption-free cutting and cleaning of threads thanks to automatic change of direction of rotation
- Quick-change tapping chuck for inserting taps with square and cylindrical shanks
- Long service life and tool life of the tappers by virtue of intelligent torque monitoring
- Metabo quick system: quick exchange of chucks, bit holders, angle adapters and more for flexible work
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Handy belt hook and bit holder can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Technical data****Characteristics**

|                             |                        |
|-----------------------------|------------------------|
| Battery voltage             | 18 V                   |
| Maximum torque, soft        | 65 Nm                  |
| Pulse torque                | 65 Nm                  |
| Maximum torque, hard        | 130 Nm                 |
| Adjustable torque           | 1 - 20 Nm              |
| Max. thread diameter        | M 12 (1/2" UNC/UNF)    |
| Drill Ø steel               | 13 mm                  |
| Drill-Ø soft wood           | 68 mm                  |
| No-load speeds              | 0 - 550 / 0 - 2000 rpm |
| Collar diameter             | 13 mm                  |
| Weight without battery pack | 1.8 kg                 |
| Weight with battery pack    | 2.2 kg                 |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 2.2 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 76 dB(A) |
| Sound power level (LwA)      | 87 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

**Scope of delivery**

Quick-change tapping chuck M4-M6  
Quick-change tapping chuck M8-M12  
Side handle  
Belt hook and bit case