

## WPB 13-125 Quick (603631190) Angle grinder Cardboard box

Order no. 603631190 EAN 4061792176393



Product may differ from Image











- Long service life for demanding applications: powerful and robust angle grinder with highest power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated non-slip switch
- Fastest brake system for highest user safety: patented, mechanical disc brake stops the disc within 2 seconds after switching off, even in the event of a power cut
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



| Technical data               |                      |
|------------------------------|----------------------|
| Characteristics              |                      |
| Disc-Ø                       | 125 mm               |
| Rated input power            | 1300 W               |
| Output power                 | 820 W                |
| No-load speed                | 11000 rpm            |
| Speed at rated load          | 8000 rpm             |
| Torque                       | 3.4 Nm               |
| Spindle thread               | M 14                 |
| Handle circumference         | 197 mm               |
| Weight (without power cable) | 2.6 kg               |
| Cable length                 | 4 m                  |
| Vibration                    |                      |
| Surface grinding             | 6 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Noise emission               |                      |
| Sound pressure level         | 93 dB(A)             |
| Sound power level (LwA)      | 104 dB(A)            |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2