

## LSV 5-225 Comfort (600136000) Long-neck sander Plastic Carry Case; with Variable Length Adjustment

Order no. 600136000  
EAN 4007430282675



Product may differ from Image



- For convenient sanding of primed surfaces on walls or ceilings
- Optional LED side light to help detect imperfections and serrations
- Optimum balance when working, as the centre of gravity of the machine is not at the sanding head
- Variable length adjustment: can be shortened or extended without tools for narrow rooms or high ceiling rooms
- Extendable to a total length of 2.1 m with additional extension (accessory)
- M-Clean technology: Effective extraction through the machine housing for maximum flexibility of the sanding head
- Ideal adaptation of the flexible sanding head to the surface for good work results
- Optimum extraction results thanks to spring-mounted brush rim that adapts to the surface.
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Ergonomically shaped aluminium handle bar and T-handle for comfortable use in different positions
- Simple, quick and tool-free exchangeable shaft can be adjusted directly on site if needed
- Putting the machine down without kinking the hose and cable
- With extensive range of grinding media for every application
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

## Technical data

### Characteristics

Sanding disc diameter	225 mm
No-load speed	1000 - 1650 rpm
Rated input power	500 W
Output power	270 W
Adjustable machine length	1.1 / 1.6 / 2.1 m
Weight (without power cable)	4.5 kg
Cable length	4 m

### Vibration

Surface grinding	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	76 dB(A)
Sound power level (LwA)	87 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Sanding pad (very soft)  
 Hook and loop sanding sheets with multi-perforation (1 each of P80, P100, P120, P150)  
 Flexible shaft (as replacement)  
 Coupling bush  
 Extension  
 Hexagonal wrench  
 Plastic carry case