

## KHA 18 LTX BL 40 (600752840) Cordless hammer 18V; Plastic Carry Case

Order no. 600752840  
EAN 4061792199934



Product may differ from Image



- Cordless hammer with SDS max holder for extremely powerful hammer drilling and chiselling - any time and anywhere
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): working, also continuously, in a low-fatigue manner whilst protecting the user's health
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Vario Constamatic (VTC) Electronics for drilling jobs in materials requiring customised speeds, which remain almost constant under load
- Optional reduction of speed and impact energy for working in softer materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- With attachment point for tool safety straps for working at great heights
- LED work light for optimum view of the drilling site
- Low-dust chiselling and drilling with external dust extraction ESA max (accessories)
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

Battery voltage	18 V
Max. single blow energy (EPTA)	8.6 J
Maximum impact rate	3200 bpm
Drill-Ø concrete with hammer drills	40 mm
Drill-Ø masonry with core bits	105 mm
No-load speed	450 - 580 rpm
Bit retainer	SDS-max
Weight without battery pack	6.9 kg
Weight with battery pack	7.9 kg

### Vibration

Hammer drilling concrete	12.5 m/s <sup>2</sup>
Uncertainty of measurement K	4.2 m/s <sup>2</sup>
Chiseling	8.5 m/s <sup>2</sup>
Uncertainty of measurement K	3.2 m/s <sup>2</sup>

### Noise emission

Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

rubber-coated side handle  
 Side handle  
 Drilling depth guide  
 Lubricant for tool shank end  
 Duster  
 Plastic carry case  
 without battery pack, without charger