

## SRE 4351 TurboTec (611351000) Orbital sander Cardboard box

Order no. 611351000  
EAN 4007430214232



Product may differ from Image

- Excellent sanding finish without scoring marks and grooves, for a professional surface finish
- Oscillating system with double-row angular ball bearing for extremely smooth running and minimum vibration
- Robust clamping system for sanding paper with or without hook and loop fastener, as well as sanding medium up to 10 mm in thickness
- Ball bearing with multiple sealings and tear-proof rubber sleeve protects the machine against aggressive dust
- Side handle with vibration damping for a comfortable grip in any work position
- TurboBoost: allows additional power reserves to be employed for maximum removal
- Vario (V)-Electronics for working at customised orbital frequencies to suit various application materials
- Sanding plate with additional lateral extraction channels for cleaner working
- Dust cartridge with filter for working without connecting to a vacuum cleaner
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

**Technical data****Characteristics**

|                                |                          |
|--------------------------------|--------------------------|
| Base plate                     | 114 x 229 mm (1/2 sheet) |
| Rated input power              | 350 W                    |
| No-load speed                  | 4200 - 11000 rpm         |
| Orbital frequency with no load | 8400 - 22000 rpm         |
| Orbit diameter                 | 2.2 mm                   |
| Weight (without power cable)   | 2.6 kg                   |
| Cable length                   | 4 m                      |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 3.3 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 79 dB(A) |
| Sound power level (LwA)      | 90 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

**Scope of delivery**

Hook and loop grinding plate  
removable side handle  
Textile dust bags