

KS 66 FS (601066000) Circular saw

Cardboard box

Order no. 601066000
EAN 4061792007475



Product may differ from Image



- Robust circular saw, can be used directly on guide rails from Metabo and also Mafell, Bosch, Festool, Makita, HiKOKI, Hilti and other manufacturers
- Fast, precise cross cuts thanks to easy coupling with a Metabo cross cutting rail
- Light guide plate made from die cast aluminium
- Grip area with non-slip soft-grip surface
- Clearly visible cutting indicator for precise sawing after initial cut
- 0° position re-adjustable for highest cutting precision
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Sawdust ejection nozzle for any working position can be rotated and locked individually
- Precision guide rail available as accessory

Technical data

Characteristics

Rated input power	1500 W
Output power	840 W
Maximum cutting depth at 90°	66 mm
Maximum cutting depth at 45°	47 mm
Max. cutting depth with guide rail	61 mm
Saw blade Ø x bore	190 x 30 mm
Swivel range from / to:	0 / + 47 °
No-load speed	5000 rpm
Speed at rated load	3800 rpm
Max. cutting speed	50 m/s
Weight (without power cable)	4.9 kg
Cable length	4 m

Noise emission

Sound pressure level	95 dB(A)
Sound power level (LwA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide circular saw blade (24 teeth)
 Parallel guide
 Hexagonal wrench