






# **Boost performance with**

For Highest Performance, Productivity and Safety:

### THE GRINDER ADVANTAGE





# "The Metabo System"

Pair Metabo Angle Grinders and Abrasives



Fast and reliable results




Longer life, improved productivity



Unstoppable, unmatched productivity





# **Metabo Cutting Wheels**



### **Product specifications**

#### Specification:

The combination of letters and numbers is the genetic code of the grinding wheel.

#### Abrasive:

- A Aluminium Oxide
  - For general processing of metal

#### ZA Zirconia Alumina

- Special discs for metal processing
- C Silicon carbide
  - For processing stone

#### **CA Ceramic**

■ Special discs for processing stainless steel and metal

The higher the number, the finer the grit. We use grain sizes of 16 - 60 for cutting and grinding discs:

16 - 24 coarse

30 – 60 medium

#### Hardness

The hardness of a grinding tool is coded alphabetically:

A B C ... NOP... RST...Z

Very soft Soft hard Very hard



Disc label with all product and safety information

Fiberglass fabric for more safety during the cutting process

Mixture with high-quality corundum, filler materials and phenolic resins

Additional fiber glass fabric for even more safety

### HEAVY DUTY

### SUPER DUTY

### EXTREME DUTY

Fast and reliable results

Longer life, improved productivity

Unstoppable, unmatched productivity

### Original Slicer

Fast, cool cutting, burr free



### Slicer-Plus

Fast cutting, long life, most versatile

# metabo

### **Ceramic Cutting**

Extremely fast, longest life, toughest conditions. lowest total cost







Size

### Type 1 and 27 Cutting Wheels

TYPE 27 Order #

NOTE: Numbers in parenthesis ( ) are for when Type 27 wheel specs are different

Pcs/Pkg

Max. RPM

HEAVY DUTY



### Original - A60TZ - Steel / Stainless Steel

Aluminum oxide wheel for steel and other ferrous metals.
Extremely fast rate of cut. Good wheel life. Flexibility for flush cutting.

,		,		
TYPE 1 Order #	TYPE 27 Order #			
655331000	655346000	4 1/2 × .040 (.045) × 7/8	15,000 (13,300)	100 (50)
655334000	655353000	5 x .040 (.045) x 7/8	12,225	50
655999000		6 X .040 X 3/8	14,000	50
655338000		6 X .040 X 5/8	10,200	50
655339000	655347000	6 x .040( .045) x 7/8	10,200	50



#### Original - A30R - Steel

TYPE 1 Order #

Aluminum oxide general purpose wheel for heavier working conditions for steel and other ferrous metals. Very fast rate of cut. Good wheel life.

TYPE 1 Order #	TYPE 27 Order #			
655733000		5 X 1/16 x 7/8	12,225	50
616732000	616310000	5 X 3/32 x 7/8	12,300	25



### Long Life - A36XL / A60XL - Steel / Stainless Steel

Engineered aluminum oxide wheel for long life in tough applications: thin wall pipe/tube, as well as solids.

PE 1 Order #	TYPE 27 Order #			
655332000 (A60XL)	655349000 (A60XL)	4 1/2 x .045 (1/16) x 7/8	15,000 (13,300)	100 (50)
<b>655335000</b> (A60XL)	<b>655355000</b> (A60XL)	5 x .045 (1/16) x 7/8	12,225	50
<b>655344000</b> (A60XL)	<b>655350000</b> (A60XL)	6 x .045 (1/16) x 7/8	10,200	50
<b>655342000</b> (A60XL)		6 X 1/16 X 5/8	10,200	25





### Plus - A60TX - Steel / Stainless Steel

Heavy duty performance on stainless steel applications.

TYPE 1 Order #	TYPE 27 Order #			
655997000	655351000	4 1/2 x .045 x 7/8	15,000 (13,300)	50
655993000	655357000	5 x .045 x 7/8	12,225	50
655998000	655352000	6 x .045 x 7/8	10,200	50



#### Super - A60XP - Steel / Stainless Steel

 Contaminant free, heavy duty wheel for steel and stainless steel applications with a long wheel life.

TYPE 1 Order #	TYPE 27 Order #			
655994000	655897000	4 1/2 x .045 x 7/8	15,000 (13,300)	50
655992000	655898000	5 x .045 x 7/8	12,225	50
655995000	655899000	6 x .045 x 7/8	10,200	50

### **Ceramic Type 1 and 27 Cutting Wheels**

### Contaminant Free < 0.1% Iron, Sulfur and Chlorine

TYPE 1 Order # TYPE 27 Order #

Size

Max. RPM

Pcs/Pkg





### M-Calibur - CA46U - Steel / Stainless Steel / High Tensile Alloy

Contaminant free, extreme heavy duty ceramic wheel for steel and stainless steel. Extremely long wheel life.

US616280000	US616272000	4 1/2 X .045 X 7/8	13,300	25
US616285000		4 1/2 X 1/16 X 7/8	13,300	25
US616283000	US616273000	5 X .045 X 7/8	12,200	25
US616286000		5 X 1/16 X 7/8	12,200	25
US616284000	US616274000	6 X .045 X 7/8	10,200	25
US616287000		6 X 1/16 X 7/8	10,200	25

### Type 1 and 27 Cutting Wheels for Aluminum

TYPE 1 Order # TYPE 27 Order	r# Size	Max. RPM	Pcs/Pkg





#### Plus-Alu - A46N - Aluminum

■ Heavy duty speciality wheel for enhanced performance on aluminum.

655811000	655821000	4-1/2 X .040 X 7/8	13,000	50
655812000	655822000	5 X .040 X 7/8	12,300	50
655813000	655823000	6 X .040 X 7/8	10,200	50
655814000	655824000	7 X .040 X 7/8	8,500	50

### Type 1 Cutting Wheels for Circular Saws

Order # Size Max. RPM Pcs/Pkg





### Original - A30S - Steel / Stainless Steel

Aluminum oxide wheels for steel, other ferrous metals and rail track. Good rate of cut.
Longer wheel life.

616331420	6 X 1/8 X 5/8 DM	10,200	25
616333000	7 X 1/8 X 5/8 DM	8,500	10



### Original - C30S - Masonry / Non-Ferrous

 Silicon carbide general purpose wheel for stone, concrete, cast iron, ductile iron, masonry materials, non-ferrous metals, brass, bronze, etc. Good rate of cut. Good wheel life.

616334000	7 X 1/8 X 5/8 DM	8.500	10

### Type 27 Cutting Wheels and Speciality Wheels

Order # Size Max. RPM Pcs/Pkg



#### Original - A30R - Steel

Aluminum oxide general purpose wheel for heavier working conditions for steel and other ferrous metals. Very fast rate of cut. Good wheel life.

US616727000	4-1/2 X 3/32 X 7/8	13,300	25
655727000	4-1/2 X 3/32 X 5/8-11	13,300	25
616310000	5 X 3/32 X 7/8	12,300	25
655310000	5 X 3/32 X 5/8-11	12,300	25
US616313000	6 X 1/8 X 7/8	10,200	25
655313000	6 X 1/8 X 5/8-11	10,200	25
616300000	7 X 1/8 X 7/8	8,500	10
655300000	7 X 1/8 X 5/8-11	8,500	10
616302000	9 X 1/8 X 7/8	6,600	10
655302000	9 X 1/8 X 5/8-11	6,600	10





#### Plus - A46TZ - Steel / Stainless Steel

Aluminum oxide general purpose wheel for steel and other ferrous metals.
Aggressive cut. Excellent wheel life.

655801000	7 X 1/16 X 7/8	8,500	10	
655802000	7 X 1/16 X 5/8-11	8,500	10	
655797000	9 X 1/16 X 7/8	6,600	10	
655799000	9 X 1/16 X 5/8-11	6,600	10	





#### Original - C30S - Masonry / Non-Ferrous

 Silicon carbide general purpose wheel for stone, concrete, cast iron, ductile iron, masonry materials, non-ferrous metals, brass, bronze, etc. Good rate of cut. Good wheel life.

materials, non forreas m	otalo, braco, bronzo,	010. 0000 1010 01 00	t. Good Wildol IIIo.	
655303000	9 x 1/8 x 5/8-11	6,600	10	



### Type 27 Pipeline Grinding/Notching/Cutting Wheels

Order # Size Max. RPM Pcs/Pkg





### Long Life - A24T - Steel / Stainless Steel

Aluminum oxide general purpose wheel for steel and other ferrous metals. Extremely long wheel life.

616281420	4-1/2 X 1/8 X 7/8	13,300	25
655281000	4-1/2 X 1/8 X 5/8-11	13,300	25
655287000	5 X 1/8 X 7/8	12,200	25
655288000	5 X 1/8 X 5/8-11	12,200	25
655285000	6 X 1/8 X 7/8	10,200	25
655282000	7 X 1/8 X 5/8- 11	8,500	10
655284000	9 X 1/8 X 5/8- 11	6,600	10





#### Plus-Z - ZA24T - Steel / Stainless Steel

Zirconia alumina wheels for steel and stainless steel applications.
Very aggressive stock removal. Extremely long wheel life.

655792000	4-1/2 X 1/8 X 5/8-11	13,300	25
616794420	6 X 1/8 X 7/8	10,200	25
655794000	6 X 1/8 X 5/8-11	10,200	25
655795000	7 X 1/8 X 5/8-11	8.500	10



### Type 27 Combinator: Cutting & Grinding with the Same Wheel

Order # Size Max. RPM Pcs/Pkg





#### Combinator - A46U - Steel/Stainless Steel

Aluminum oxide, contaminant free for stainless steel and other ferrous metals. Extremely long wheel life, and fast cut.

616500420	4-1/2 X 5/64 X 7/8	13,300	25
616501420	5 X 5/64 X 7/8	12,300	25
616502420	6 X 5/64 X 7/8	10,200	25

### **Type 1 Cutting Wheels for Chop Saws**

Order# Size Max.RPM Pcs/Pkg Formula Wheel





#### Original - A24M

Aluminum oxide wheels for general purpose use on steel and other ferrous metals larger chop saw applications. Excellent rate of cut. Good wheel life.

#### Original - A30P

Aluminum oxide wheels constructed with a single internal reinforcement and an aggressive cool cutting formulation best for cutting smaller diameter metals or metal studs.

### Original Long Life - A30R

Aluminum oxide wheels for general purpose use on steel and other ferrous metals. Good rate of cut. Good wheel life.

#### Original Long Life - A30S

Aluminum oxide wheels specially formulated for dry wall stud applications. Good rate of cut. Good wheel life.

616340000	14 X 3/32 X 1	4,300	10	A24M	Original
655236000	14 X 3/32 X 1 Internal Reinforced	4,300	10	A30P	Original
616215000	16 X 3/32 X 1	3,820	10	A24M	Original
616337420	12 X 3/32 X 1	5,100	10	A30R	Original Long Life
616146000	14 X 3/32 X 1	4,300	10	A30S	Original Long Life
US616338000	14 X 3/32 X 1	4,300	10	A30R	Original Long Life

### Type 1 Cutting Wheels for High Speed Saws

Order # Size Max. RPM Pcs/Pkg Formula Wheel





#### Original - A24N

Aluminum oxide wheels general purpose for steel and other ferrous metals.
Fast rate of cut. Good wheel life.

#### **Original Long Life - A30S**

Aluminum oxide wheels for steel, other ferrous metals and rail track.
Good rate of cut. Longer wheel life.

#### Original - C24N

 Silicon carbide general purpose wheel for stone, concrete, cast iron, ductile iron, masonry materials, non-ferrous metals, brass, bronze, plastic, etc. Fast rate of cut. Good wheel life.

#### Plus - AC24R

 Aluminum oxide and Silicon carbide combination wheel specially formulated for ductile iron. Excellent rate of cut. Excellent wheel life.
Smooth and chatter free cutting.

US616136000	12 X 1/8 X 20mm	6,400	10	A24N	Original
616159000	14 X 1/8 X 1	5,400	10	C24N	Original
616140000	14 X 1/8 X 20mm	5,460	10	A24N	Original
616160000	14 X 1/8 X 20mm	5,460	10	C24N	Original
616149000	14 X 1/8 X 1	5,400	10	AC24R	Plus
616142000	14 X 1/8 X 20mm	5,460	10	AC24R	Plus

655172000 Reduced bushing from 1" to 20mm

### Type 1 Cutting Wheels for Stationary Saws

Order # Size Max. RPM Pcs/Pkg Formula Wheel





### Original - A30N

 Aluminum oxide wheels are specially formulated for high powered tools to cut steel and other ferrous metals. Excellent rate of cut. Good wheel life

### Original Long Life - A30R

Aluminum oxide wheels specially formulated for high powered tools to cut steel and other ferrous metals. Fast rate of cut. Longer wheel life.

#### Original Long Life - A30S

Aluminum oxide wheels for steel, other ferrous metals and rail track. Good rate of cut. Longer wheel life.

#### Plus - A30V

Aluminum oxide wheels are specially formulated for high powered tools to cut steel and other ferrous metals. Good rate of cut. Excellent wheel life.

616365000	20 X 3/16 X 1	4,800	5	A30N	Original
616203000	14 X 1/8 X 1	4,400	10	A30S	Original Long Life
616366000	20 X 3/16 X 1	3,000	5	A30R	Original Long Life
616367000	20 X 3/16 X 1	3,000	5	A30V	Plus

### **Angle Grinder Accessories**

### **SHROUDS**



626732000 5" Convertible shroud for concrete grinding. Fits all Metabo W9, 12, 15, 17, 19 series arinders



Dustless convertible shroud for concrete surface prep

655154000 For all current large angle grinders W 24 / W 26

**655153000** For all current small angle grinders W 9 / W 12 / W 15 / W 17



626731000 CED 125 Plus Anti-Static Shroud for concrete cutting with guide rail



628216000 **Dustless Tuck Point Guard** Fits small angle grinders, W 9/W 12/W 15/W 17



631166000 for 7" Max. cutting depth 1-5/8"

631167000 for 9" Max. cutting depth 2-5/8". Extraction guards for cutting stone, concrete, masonry Fit Large angle grinders, W 22 / W 24 / W 26 versions

### **GUARDS**



Quick-clip on type 1 cutting guard

630351000 - 4 1/2" 630352000 - 5" **630353000** - 6"

Fits W9, W/WP/WPB12, W1200, WE/WEP/WEPBA15, WEV1500, WE/WEP/WEPBA17 series grinders Type 1 steel cut-off wheel guard

4 1/2" US339203030

5" US339203040

6" US339203050

7" 630383000 (For WEPBA 19 & WPB 36)

7" 630356000 (For W 24 MVT series) 9" 630357000 (For W 24 / W 26 MVT series)

9" **630363000** (For WPB 36 only) (Does not fit W 750/W 850/W 1100/ W 1200/W 1500)

Cup wheel guard and flange for mounting 4" - 6" Type 11 cup wheels on 7" - 9" angle grinders Guards: 655174000 - 4"/5", **655178000** - 6". Mounting flange US90357006



623276000 Cup wheel guard for mounting 3 1/8" Type 6 cup wheels on 4 1/2" - 6" angle grinders

### ADAPTOR KITS AND SPANNER WRENCH



655039000 Adaptor kit for 7" - 9" Type 27 wheels w/o hub. 655052000 replacement nut



US655038000 Adaptor kit for diamond blades on 7" - 9" grinders



623934000 Straight 623910000 Offset



630327000 hand guard for use on all polishers, angle sanders and grinders

### **HANDLES**



627362000 Multiple Position Bar The 180 degree bar allows for infinite adjustment of the side handle



US630342000 Loop handle for - 9" angle sander & grinders 141110390 bolts to attach loop handle (2 required), sold separately



623262000 Loop handle for small grinders Fits W/WP9, WE/WEV/WEVF 10, W/WP/WPB 12, WE/WEV/WEF/WEPF/WEPBF 15, WEP/WEPBA 17 grinders

### **BACKING PADS**

#### Flexible backing pads for using abrasive discs on angle sanders and grinders. 623279000 - 4 1/2" w/ M14-2.0 nut

623283000 - 4 1/2" w/ 5/8-11 nut 623284000 - 5" w/ 5/8-11 nut

623281000 - 7" w/ 5/8-11 nut 623282000 - 9" w/ 5/8-11 nut



**DUST PROTECTION FILTERS** 

630709000 Lock-on switch models



630792000 Paddle switch models



Rat-tail models

# **Metabo Grinding Wheels**







Available in a wide range of sizes; 3" to 9" diameter in Type 27 depressed center wheels.



### **Type 27 Depressed Center Grinding Wheels**

Steel, Stainless Steel

Order # Size Max. RPM Pcs/Pkg





#### Original - A24N - Steel

 Aluminum oxide general purpose wheel for grinding steel and other ferrous metals in normal working conditions. High stock removal. Good wheel life.

US616745000	4 X 1/4 X 5/8	15,300	25
US616726000	4-1/2 X 1/4 X 7/8	13,300	25
655726000	4-1/2 X 1/4 X 5/8-11	13,300	25
655730000	5 X 1/4 X 5/8-11	12,200	25
US616730000	5 X 1/4 X 7/8	12,200	25
US616554000	6 X 1/4 X 7/8	10,200	25
655554000	6 X 1/4 X 5/8-11	10,200	25
US616560000	7 X 1/4 X 7/8	8,500	25
655560000	7 X 1/4 X 5/8-11	8,500	10
US616572000	9 X 1/4 X 7/8	6,600	25
655572000	9 X 1/4 X 5/8-11	6,600	10





#### Long Life - A24R - Steel

 Aluminum oxide general purpose wheel for grinding steel and other ferrous metals in normal working conditions. High stock removal. Long wheel life.

616339420	4 X 1/4 X 3/8	15,300	25
616330000	4 X 1/4 X 5/8	15,300	25
616307000	4-1/2 X 1/4 X 7/8	13,300	25
655307000	4-1/2 X 1/4 X 5/8-11	13,300	25
616308000	5 x 1/4 x 7/8	12,200	25
655308000	5 X 1/4 X 5/8-11	12,200	25
616319000	6 X 1/4 X 7/8	10,200	25
655319000	6 X 1/4 X 5/8-11	10,200	25
616782000	7 X 1/4 X 7/8	8,500	10
655782000	7 X 1/4 X 5/8-11	8,500	10
616784000	9 X 1/4 X 7/8	6,600	10
655784000	9 X 1/4 X 5/8-11	6,600	10





#### Plus-Z - ZA24T - Steel / Stainless Steel

 Zirconia alumina wheels for steel and stainless steel applications. Very aggressive stock removal. Extremely long wheel life.

616785000	4-1/2 X 1/4 X 7/8	13,300	25
655785000	4-1/2 X 1/4 X 5/8-11	13,300	25
616787000	6 X 1/4 X 7/8	10,200	25
655787000	6 X 1/4 X 5/8-11	10,200	25
655788000	7 X 1/4 X 5/8-11	8,500	10
655789000	9 X 1/4 X 5/8-11	6,600	10



### Type 27 Grinding Wheels for Stainless Steel

Contaminant Free < 0.1% Iron, Sulfur and Chlorine

Order#

Size

Max. RPM

Pcs/Pkg





Super - A360 - Steel / Stainless Steel / High Tensile Alloy

Contaminant free, Super Duty aluminum oxide wheel specially formulated for harder metals such as stainless steel. Good stock removal. Good wheel life.

616739000	4-1/2 x 1/4 x 7/8	13,300	25
US616747000	5 x 1/4 x 7/8	12,200	25
US616604000	6 X 1/4 X 7/8	10,200	25
655610000	7 X 1/4 X 5/8-11	8,500	10





#### M-Calibur - CA46U - Steel / Stainless Steel / High Tensile Alloy

Contaminant free, Extreme Duty ceramic wheel for steel and stainless steel. Extremely long wheel life.

US616290000	4-1/2 x 1/4 x 7/8	13,300	10
US655290000	4-1/2 x 1/4 x 5/8-11	13,300	10
US616291000	5 x 1/4 x 7/8	12,300	10
US616292000	6 x 1/4 x 7/8	10,200	10
US655292000	6 x 1/4 x 5/8-11	10,200	10



### **Type 27 Specialty Grinding Wheels**

Aluminum

Order# Size Max. RPM Pcs/Pkg





#### Plus - A36M - Aluminum

 Aluminum oxide wheel formulated for aluminum grinding applications. Good stock removal. Good wheel life. Non clogging capability.

US616748000	4-1/2 X 1/4 X 7/8	13,300	25	
655748000	4-1/2 X 1/4 X 5/8- 11	13,300	25	
616749000	5 X 1/4 X 7/8	12,200	25	
LIS616754000	6 X 1/4 X 7/8	10 200	25	



### **Type 6 Cup Wheels for Angle Grinders**

Order#

Size

Max. RPM

Pcs/Pkg

Formula



#### M08A

Aluminum oxide general purpose wheel for grinding steel and other ferrous metals. Good cutting rate and wheel life.

#### C30N

 Silicon carbide general purpose wheel for grinding stone, concrete, ductile iron, masonry materials, non-ferrous metals (brass, bronze, etc.), and cast iron. Good stock removal.
Good wheel life.

630727000	3-1/8 x 7/8 x 7/8	10,750	1	A 80 M
630728000	3-1/8 x 7/8 x 7/8	10,750	1	C 30 N



# Type 11 Cup Wheels with Steel Backs for Angle Grinders

Order#

Size

Max. RPM

Pcs/Pkg

Formula



#### A16Q

Aluminum oxide general purpose wheel for grinding steel and other ferrous metals. High stock removal. Good wheel life.

#### **C16N**

 Silicon carbide general purpose wheel for grinding stone, concrete, ductile iron, masonry materials, non-ferrous metals (brass, bronze, etc.) and cast iron. High stock removal.
Good wheel life.

#### **ZA16**


Zirconia alumina for aggressive stock removal and extra long wheel life grinding steel and stainless steel.

616341119	4 x 3 x 2 x 5/8-11	9,000	10	A 16 Q
616342119	4 x 3 x 2 x 5/8-11	9,000	10	C 16 N
616343119	5 x 4 x 2 x 5/8-11	7,200	10	A 16 Q
616345119	6 x 4-3/4 x 2 x 5/8-11	6,000	10	A 16 Q
616347119	6 x 4-3/4 x 2 x 5/8-11	6,000	10	ZA 16 T



# **Metabo Flap Discs**







623178000





120 grit: special order, previous design

### **Original Flapper**

Fast stock removal, one step blending and finishing



- Steel / Stainless
- Ferrous metal
- High performance Zirconia blend

**Contaminant Free** 

	7/	8″		5/8″-11 (	hubbed)	
Grit	Type 29	Type 27	Pack	Type 29	Type 27	Pack
40	629405000	629467000	10	629401000	629464000	5
60	629406000	629468000	10	629402000	629465000	5
80	629/07000	629/69000	10	629403000	629466000	5

656455000

### Flapper Plus

Aggressive stock removal, long life, most versatile, one step blending and finishing, cool grinding



- Steel / Stainless
- Heat sensitive material
- Glaze resistant
- Premium Zirconia and high flap density for increased performance and longer life

**Contaminant Free** 

	7/8"			5/8"-11 (hubbed)		
Grit	Type 29	Type 27	Pack	Type 29	Type 27	Pack
36	629418000	629480000	10	629408000	629470000	5
40	629419000	629481000	10	629409000	629471000	5
60	629420000	629482000	10	629410000	629472000	5
80	629421000	629483000	10	629411000	629473000	5
120	656427000	656425000	10	656428000	656426000	5

### Flapper Plus JUMBO

Based on the flapper plus technology, this exceptional wheel contains 62% more flaps for unbeatable wheel life.





JUMBO vs. Standard



	7/8"			5/8″-11 (	hubbed)	
Grit	Type 29	Type 27	Pack	Type 29	Type 27	Pack
40	629431000	629490000	5	629425000	629487000	5
60	629432000	629491000	5	629426000	629488000	5
80	629433000	629492000	5	629427000	629489000	5
120	656429000		10			

### **Ceramic Flapper**

Highest performance, cool operation



- Hardened metals
- Stainless steel
- High tensile alloys
- Hastalloys
- Inconels
- Titanium
- terial

	7/	8"	
Grit	Type 29	Type 27	Pack
40	629437000	629493000	10
60	629438000	629494000	10
80	629439000	629495000	10

### Flapper Plus Trimmable

		5/8"-11 (hubbed)	
meiabo	Grit	Type 29	Pack
	40	629446000	5
	60	629447000	5
16	80	629448000	5

### Ceramic Flapper Trimmable

		5/8"-11 (hubbed)	
metabo	Grit	Type 29	Pack
	40	629455000	5
	60	629456000	5
	80	629457000	5





### Ceramic Flapper



	7/8″		
Grit	Type 29	Pack	
40	629440000	10	
60	629441000	10	
80	629442000	10	

### Flapper Plus Trimmable



	5/8"-11 (Hubbed)	
Grit	Type 29	Pack
40	629449000	5
60	629450000	5
80	629451000	5

### **Ceramic Flapper** *Trimmable*



	5/8"-11 (hubbed)	
Grit	Type 29	Pack
40	629458000	5
60	629459000	5
80	629460000	5

6"

### Flapper Plus



	7/	8″		5/8"-11 (hubbed)				
Grit	Type 29	Type 27	Pack	Type 29	Type 27	Pack		
40	629422000	629484000	10	629412000	629474000	5		
60	629423000	629485000	10	629413000	629475000	5		
80	629424000	629486000	10	629414000	629476000	5		
120	656433000		10	656437000		5		

**Ceramic Flapper** 



	7/	/8″	
Gri	t Type 29	Type 27	Pack
40	629443000	629499000	10
60	629444000	629500000	10
80	629445000	629501000	10

120 grit: special order, previous design

### Flapper Plus Trimmable



	5/8"-11 (hubbed)	
Grit	Type 29	Pack
40	629452000	5
60	629453000	5
80	629454000	5

### Ceramic Flapper Trimmable



	5/8"-11 (hubbed)	
Grit	Type 29	Pack
40	629461000	5
60	629462000	5
80	629463000	5

7"

### Original Flapper



	5/8"-11 (hubbed)	
Grit	Type 29	Pack
40	629404000	5

### Flapper Plus



	5/8"-11 (hubbed)				
Grit	Type 29	Type 27	Pack		
40	629415000	629477000	5		
60	629416000	629478000	5		
80	629417000	629479000	5		

### Flapper Plus JUMBO



	5/8"-11 (hubbed)		
Grit Type 29		Pack	
40	629428000	5	
60	629429000	5	
80	629430000	5	

### **Ceramic Flapper**



	5/8"-11 (hubbed)	
Grit	Type 29	Pack
40	629434000	5
60	629435000	5
80	629436000	5







### **Resin Fiber Abrasives Discs - Closed Coat**

Aluminum Oxide (A) - General purpose disc for grinding steel and other ferrous metals. Good cutting rate and excellent life. Zirconia Alumina (ZA) - Very aggressive stock removal on steel, stainless steel and other metal applications, extremely long life, cooler grinding.

Ceramic Grain (CER) - Offers extremely high removal rates and extreme longevity, especially when grinding Stainless Steels, Titanium, Inconel and Alloy Steels.













		Disc Size	Grit	Slotted Order #	Grit	Non-Slotted Order #	Grit	Slotted Order #	
		4-1/2 x 7/8	A16	624135000	ZA16				
		4-1/2 x 7/8	A24	624136000	ZA24	656350000			
		4-1/2 x 7/8	A36		ZA36	656351000	CER36	626151000	
	o >	4-1/2 x 7/8	A40	624137000	ZA40				
	623283000 13,000 RPM	4-1/2 x 7/8	A50	624144000	ZA50	656352000			
	<b>623283</b> 13,000	4-1/2 x 7/8	A60	624138000	ZA60	656353000	CER60	626152000	
	62; 13,(	4-1/2 x 7/8	A80	624139000	ZA80	656354000	CER80	626153000	
		4-1/2 x 7/8	A100	624140000	ZA100				
		4-1/2 x 7/8	A120	624141000	ZA120				
		4-1/2 x 7/8	A150	624142000	ZA150				
		4-1/2 x 7/8	A180	624143000	ZA180				
		5 x 7/8	A16	624223000	ZA16				
		5 x 7/8	A24	624218000	ZA24	656355000	CER24	626154000	
S		5 x 7/8	A36		ZA36	656356000	CER36	626155000	
ads	<u> </u>	5 x 7/8	A40	624219000	ZA40				
•	0 ≥	F 7/0	A F.O.	004047000	7450	CEC0E7000			



	300	4-1/2 x 7/8	A50	624144000	ZA50	656352000		
	62328300 13,000 RF	4-1/2 x 7/8	A60	624138000	ZA60	656353000	CER60	626152000
	62; 13,(	4-1/2 x 7/8	A80	624139000	ZA80	656354000	CER80	626153000
		4-1/2 x 7/8	A100	624140000	ZA100			
		4-1/2 x 7/8	A120	624141000	ZA120			
		4-1/2 x 7/8	A150	624142000	ZA150			
		4-1/2 x 7/8	A180	624143000	ZA180			
		5 x 7/8	A16	624223000	ZA16			
		5 x 7/8	A24	624218000	ZA24	656355000	CER24	626154000
· ·		5 x 7/8	A36		ZA36	656356000	CER36	626155000
ğ	0.5	5 x 7/8	A40	624219000	ZA40			
Backing Pads	<b>623284000</b> 12,000 RPM	5 x 7/8	A50	624217000	ZA50	656357000		
	284	5 x 7/8	A60	624220000	ZA60	656358000	CER60	626156000
	623 12,0	5 x 7/8	A80	624221000	ZA80	656359000	CER80	626157000
ä	,	5 x 7/8	A100	624222000				
ш		5 x 7/8	A120	624224000				
		5 x 7/8	A150	624225000				
		5 x 7/8	A180	624226000				
		7 x 7/8	A24	624103000				
	0.5	7 x 7/8	A36		ZA36	656361000	CER36	626159000
	900 7P.N	7 x 7/8	A40	624104000	ZA40			
	623281000 8,500 RPM	7 x 7/8	A50	624102000				
	623 3,50	7 x 7/8	A60	624105000	ZA60	656363000	CER60	626160000
		7 x 7/8	A80	624106000	ZA80	656364000	CER80	626161000
		7 x 7/8	A100	624107000				
	000 PM	9 x 7/8	A24	624227000				
	623282000 6,600 RPM	9 x 7/8	A36		ZA36	656366000		
	623	9 x 7/8	A40	624228000				
	. All I -		' 	ala saida NAAA asabaa				

Note: All sold in packs of 25 and backing pads with M14 arbor available.

## WIRE WHEELS AND BRUSHES

### For Small Angle Grinders

For Small Angle Grinders								
	Steel Order#	Stainless Order#	Dia.	Trim Length	Thread	Wire	Max RPM	Use on
	655207000		2-3/4"	1"	5/8"-11	.012 crimped	14,000	4"-6" grinders
	623796000	623801000	2-3/4"	3/4"	M14-2.0	.014 knotted	12,500	4"-6" grinders
		623805000	2-3/4"	3/4"	5/8"-11	.014 knotted	12,500	4"-6" grinders
	623804000		2-3/4"	3/4"	5/8"-11	.020 knotted	12,500	4"-6" grinders
Manusa (1)	655200000	655201000	2-3/4"	1"	5/8"-11	.020 knotted	14,000	4"-6" grinders
	655203000		3-1/2"	1-1/4"	5/8"-11	.014 crimped	12,000	4"-6" grinders
and Millial Porce		655205000	3-1/2"	1-1/4"	5/8"-11	.014 knotted	12,000	4"-6" grinders
	655202000	655204000	3-1/2"	7/8"	5/8"-11	.023 knotted	13,000	4"-6" grinders
	Steel Order#	Stainless Order#	Dia. x Face	Trim Length	Thread	Wire	Max RPM	Use on
. a. abbo.	655137000	655138000	4" x 3/16"	7/8"	5/8"-11	.020 knotted	20,000	4"-6" grinders
	655136000	655221000	4" x 3/8"	7/8"	5/8"-11	.020 knotted	20,000	4"-6" grinders
	655215000		4" x 1/2"	7/8"	5/8"-11	.014 knotted	20,000	4"-6" grinders
	655227000		4" x 1/2"	7/8"	5/8"-11	.014 crimped	14,000	4"-6" grinders
	655228005	655231005	4-1/2" x 3/16	" 13/16"	5/8"-11	.020 knotted	12,500	4.5"-6" grinders
AND F.	655229005	655232005	5" x 3/16"	7/8"	5/8"-11	.020 knotted	12,500	5"-6" grinders
	655230005	655233005	5" x 1/2"	7/8"	5/8"-11	.023 knotted	12,500	5"-6" grinders
	Steel Order#	Stainless Order#	Dia. x Face	Trim Length	Thread	Wire	Max RPM	Use on
	655234000	655235000	4" x 3/8"	3/4"	5/8"-11	.020 knotted	12,500	4"-6" grinders

### For Large Angle Grinders

	Steel Order#	Dia.	Trim Length	Thread	Wire	Max RPM	Use on
16 24 11V TA 18 28 28 28	655209000	4"	1-3/8"	5/8"-11	.014 crimped	9,000	7"-9" grinders
	623765000	4"	1-1/8"	5/8"-11	.023 knotted	9,000	7"-9" grinders
	655211000	6"	1-1/4"	5/8"-11	.014 crimped	6,600	7"-9" grinders
	655210000	6"	1-3/8"	5/8"-11	.023 knotted	6,600	7"-9" grinders

	Steel Order#	Stainless Order#	Dia. x Face	Trim Length	Thread	Wire	Max RPM	Use on
	655134000	655218000	6" x 5/16"	1-3/8"	5/8"-11	.023 knotted	9,000	7"-9" grinders
	655133000		6-7/8" x 3/16"	1-1/4"	5/8"-11	.020 knotted	9,000	7"-9" grinders

### **Safety Training**

### Mobile Safety Training / Jobsite Event Vehicle:

Showcasing Metabo's range of products at open houses, special events, local and regional trade shows, job-sites and training centers.



### Learn about Metabo's Safety Features

from our highly experienced team of 'Safety Experts'



Experience the cordless power of LiHD



Demo Metabo Tools and Accessories



#### **Get Trained**

Train your team about the safe use of power tools.



Schedule your FREE safety training!

1-800-638-2264



### **JOIN THE CONVERSATION!**



The Metabo Club is a community of skilled, professional tradespeople that take pride in their craft, with a deep concern for quality, performance, productivity and safety (their own and others). The Metabo Club is a forum to exchange ideas with similar-minded pros to improve their skills and get the job done. It is a place of knowledge sharing, passion and pride.

metabo.com/club

www.metabo.ca

Metabo Corporation

Phone: 610-436-5900 or 800-638-2264

Fax: 800-638-2261 info@metabousa.com www.metabo.com









Metabo Canada Inc. Phone: 905-624-5897 or 877-638-2261 Fax: 877-638-2269 info@metabo.ca

US2046 8/18

