



Range of Metabo circular saws and plunge cut circular saws

	Cutting depth				Saw blade Ø	Particular product advantages	Equipment					Applications			Saw blade recommendation												
	55 mm	57 mm	66 mm	85 mm			Brushless motor	Anti-kickback function	Brake	Compatible with guide rail	Compatible with cross cutting rail	Plunge cut	Undercut	Mitre cuts	Cross section wood	precision cut wood	Sawing into wood without tearing ²	precision cut wood	Longitudinal cuts wood	power cut wood	Universal sawing	multi cut	Sawing of aluminium	aluminium cut	Cold cuts in metals and sandwich panels	steel cut / sandwich panel „classic“	Especially for cordless circular saws
18 V Cordless circular saws and plunge cut circular saws																											
	KS 18 LTX 57	■			165 mm			■	■	■		■	0° - 50°	■	628290000	628291000	628292000	628293000	628276000	628273000	628294000 / 628295000						
	KS 18 LTX 57 BL	■			165 mm			■	■	■		■	0° - 50°	■													
	KS 18 LTX 66 BL		■		165 mm		■	■	■	■	■	■	0° - 46°	■													
	KT 18 LTX 66 BL		■		165 mm	Anti-kickback function	■	■	■	■	■	■ ¹	-1° - 46°	■													
Mains-powered circular saws and plunge cut circular saws																											
	KS 55	■			160 mm							■	0° - 47°	■	628031000	628072000	628071000	628073000	628288000								
	KS 55 FS	■			160 mm				■			■	0° - 47°	■													
	KS 66 FS		■		190 mm				■	■		■	0° - 47°	■	628035000	628035000	628005000	628077000	628296000	628682000							
	KS 85 FS			■	235 mm				■	■		■	0° - 48°	■	628494000	628494000	628493000	628495000		628681000							
	KT 66 BL		■		165 mm	Anti-kickback function	■	■	■	■	■	■ ¹	-1° - 46°	■	628290000	628291000	628292000	628293000	628276000	628273000							

¹ with lock function

² use number of teeth as high as possible