

## KHA 18 LTX BL 40 (600752840) Cordless hammer 18V; Plastic Carry Case

Order no. 600752840  
EAN 4061792199934



Product may differ from Image



- Cordless hammer with SDS max holder for extremely powerful hammer drilling and chiselling - any time and anywhere
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Vario Constamatic (VTC) Electronics for drilling jobs in materials requiring customised speeds, which remain almost constant under load
- Optional reduction of speed and impact energy for starting a drill hole or working in softer materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- With attachment point for tool safety straps for working at great heights
- LED work light for optimum view of the drilling site
- Low-dust chiselling and drilling with external dust extraction ESA max (accessories)
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                                     |               |
|-------------------------------------|---------------|
| Battery voltage                     | 18 V          |
| Max. single blow energy (EPTA)      | 8.6 J         |
| Maximum impact rate                 | 3200 bpm      |
| Drill-Ø concrete with hammer drills | 40 mm         |
| Drill-Ø masonry with core bits      | 105 mm        |
| No-load speed                       | 450 - 580 rpm |
| Bit retainer                        | SDS-max       |
| Weight without battery pack         | 6.9 kg        |
| Weight with battery pack            | 7.9 kg        |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 12.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 4.2 m/s <sup>2</sup>  |
| Chiseling                    | 8.5 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 3.2 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 94 dB(A)  |
| Sound power level (LwA)      | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

rubber-coated side handle  
 Side handle  
 Drilling depth guide  
 Lubricant for tool shank end  
 Duster  
 Plastic carry case  
 without battery pack, without charger