

BS 18 LTX-3 BL Q I Metal (603180840) Cordless drill / screwdriver 18V: metaBOX 145 L

Order no. 603180840 EAN 4061792211650



Product may differ from Image















- The metal expert: brushless, 3-speed drill with maximum power and automatically re-tightening chuck
- Extremely powerful chuck with re-tensioning function against slipping of the bit and high degree of concentricity
- Third speed setting with high torque (max. 4,000/min) for extended range of application and even faster drilling progress, especially in metal
- Metabo QuickPlus System: quick change of chucks, bit holders, angle adapters and more for flexible working with maximum
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



| Technical data | |
|------------------------------|-----------------------------------|
| Characteristics | |
| Battery voltage | 18 V |
| Maximum torque, soft | 65 Nm |
| Maximum torque, hard | 130 Nm |
| Adjustable torque | 1 - 18 Nm |
| Drill Ø steel | 16 mm |
| Drill-Ø soft wood | 68 mm |
| No-load speeds | 0 - 450 / 0 - 2000 / 0 - 4000 rpm |
| Chuck capacity | 1.5 - 13 mm |
| Collar diameter | 43 mm |
| Weight without battery pack | 2 kg |
| Weight with battery pack | 3 kg |
| Vibration | |
| Drilling in metal | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s² |
| Noise emission | |
| Sound pressure level | 75 dB(A) |
| Sound power level (LwA) | 85 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Futuro Top quick-change chuck "QuickPlus"

Side handle

C-wrench

metaBOX 145 L

without battery pack, without charger

www.metabo.com 2/2