

## WVB 18 LT BL 11-125 Quick Inox (613091850) Cordless angle grinder 18V; Cardboard box; with brake, speed control, quick-locking nut

Order no. 613091850 EAN 4061792206939



Product may differ from Image



















- Brushless cordless angle grinder of the new generation: as powerful as a 1,100 Watt mains-powered tool thanks to 40% more power
- Perfect processing of stainless steel: powerful angle grinder with high gear reduction and adjustable reduced speed for cool
- Service-free Brushless motor with highest efficiency and maximum handiness
- M-Quick System for tool-free disc change at the touch of a button
- Battery pack can be rotated in 90°steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



| Technical data               |                      |  |
|------------------------------|----------------------|--|
| Characteristics              |                      |  |
| Battery voltage              | 18 V                 |  |
| Disc-Ø                       | 125 mm               |  |
| Max. cutting depth           | 33 mm                |  |
| No-load speed                | 2000 - 7600 rpm      |  |
| Spindle thread               | M 14                 |  |
| Handle circumference         | 191 mm               |  |
| Weight without battery pack  | 1.8 kg               |  |
| Weight with battery pack     | 2.5 kg               |  |
| Vibration                    |                      |  |
| Surface grinding             | 8 m/s <sup>2</sup>   |  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |  |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |  |
| Noise emission               |                      |  |
| Sound pressure level         | 81 dB(A)             |  |
| Sound power level (LwA)      | 92 dB(A)             |  |
| Uncertainty of measurement K | 3 dB(A)              |  |

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle

**Dust Protection Filter** 

without battery pack, without charger

www.metabo.com 2 / 2