

KGS 216 M (613216380) Mitre saw (220-240 V / 50 - 60 Hz); Cardboard box; With sliding function

Order no. 613216380 EAN 4061792221253



Product may differ from Image







- Crosscut and mitre saw of the mobile M-class with sliding function light, precise, user-friendly
- Precision Cut Line (PCL): precise shadow cutting line without re-adjustment thanks to cleverly positioned LED
- Large cutting capacity thanks to sliding function for wide work pieces
- Turntable with fast, precise setting of common angles using stop points
- Saw blade inclination from -2 to 47°, therefore also suited for undercuts
- Robust die-cast aluminium design for the highest demands
- Effective dust extraction via integrated dust scoop
- Soft start for long service life of motor and drive
- Extendable table width extensions, also removable to put underneath extremely long work pieces
- Quick-action clamp for secure fixing of the work piece from the top or front
- Depth guide for easy creation of grooves
- All scales and operating elements are visible from the working position and can be operated intuitively
- Ergonomic handle areas for carrying with one or two hands

www.metabo.com 1/2



Technical data	
Characteristics	
Dimensions	710 x 476 x 512 mm
Support surface	345 x 730 mm
Maximum cutting width 90°/45°	305 / 215 mm
Maximum cutting depth at 90°/45°	70 / 40 mm
Cutting capacity 90°/90°	305 x 70 mm
Cutting capacity 45°/45°	215 x 40 mm
Turntable setting left/right	50 / 50 °
Saw blade tilt left/right	47 / 2 °
Saw blade	216 x 30 mm
Rated input power	1200 W
Rated input power S1 100%	1200 W
Rated input power S6 20%	1500 W
No-load speed	5000 rpm
Speed at rated load	3750 rpm
Cutting speed	57 m/s
Weight	13.4 kg
Cable length	2 m
Noise emission	
Sound pressure level	85 dB(A)
Sound power level (LwA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Saw blade "precision cut wood - classic", 216x30, Z40

2 Table length extensions

Length Guide

Material clamp

Tool for saw blade change

Cable winder

Chip Collection Bag

www.metabo.com 2 / 2