

## SXE 150-5.0 BL (615050380) Random orbital sander (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 615050380 EAN 4061792217195



Product may differ from Image













- Extremely light and flat random orbital sander with symmetrical design for easy change of hands or operation with two hands
- Orbit diameter 5 mm for maximum material removal with good surface quality
- Non-slip paddle switch with dead man function for safe starting and optionally also control of the speed
- Vario Tacho Constamatic (VTC) Full-wave Electronics for grinding with materials requiring customised speeds, which remain constant under load
- Electronic presetting of the desired speed range
- Soft start minimises surface damage when placing the machine on the work surface
- Unique Metabo brushless motor highest efficiency when grinding, also in continuous mode
- Low vibrations for convenient continuous mode
- Overload protection: protects the motor from overheating
- Separate main switch protects from unintentional start
- Motor and plate brake permits quick placing down of the machine after use
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Multi-hole sanding pad for effective extraction and a longer service life of the sanding medium
- When working with 125 mm sanding sheets, the sanding pad "multi-hole" Ø 125 mm can be used (accessory 630264000)
- Service-friendly with exchangeable cable

www.metabo.com 1/2



Technical data		
Characteristics		
Diameter of backing pad	150 mm	
Rated input power	350 W	
No-load speed	4000 - 10000 rpm	
Orbital frequency with no load	8000 - 20000 opm	
Orbit diameter	5 mm	
Weight (without power cable)	1 kg	
Cable length	4.3 m	
Vibration		
Surface grinding	3.4 m/s²	
Noise emission		
Sound pressure level	71 dB(A)	
Sound power level (LwA)	82 dB(A)	
Uncertainty of measurement K	2 dB(A)	

## Scope of delivery

Sanding pad "multi-hole" with hook and loop Open-jawed spanner

www.metabo.com 2 / 2