

KHE 3251 (600659000) Combination hammer

(220-240 V / 50 - 60 Hz); metaBOX 165 L; with Metabo Quick change chuck

Order no. 600659000

EAN 4007430208705



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Ergonomic housing shape for chiselling tasks without side handle
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

Technical data

Characteristics

| | |
|-------------------------------------|--------------|
| Max. single blow energy (EPTA) | 3.1 J |
| Maximum impact rate | 4470 bpm |
| Rated input power | 800 W |
| Drill-Ø concrete with hammer drills | 32 mm |
| Drill-Ø masonry with core bits | 82 mm |
| Drill Ø steel | 13 mm |
| Drill-Ø soft wood | 35 mm |
| No-load speed | 0 - 1150 rpm |
| Speed at rated load | 920 rpm |
| Bit retainer | SDS-plus |
| Collar diameter | 50 mm |
| Weight (without power cable) | 3.6 kg |
| Cable length | 4 m |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 12.9 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 10.9 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Keyless chuck for tools with cylindrical shank
 Metabo VibraTech (MVT) side handle
 Drilling depth guide
 metaBOX 165 L