

KHE 2660 Quick (600663610) Combination hammer (110-120 V / 50 - 60 Hz); metaBOX 145 L; with Metabo Quick change chuck

Order no. 600663610
EAN 4007430307798



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- Bottom switch protected against damage and dust
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation
- Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

Technical data

Characteristics

Max. single blow energy (EPTA)	3 J
Maximum impact rate	4300 bpm
Rated input power	850 W
Drill-Ø concrete with hammer drills	26 mm
Drill-Ø masonry with core bits	68 mm
Drill Ø steel	13 mm
Drill-Ø soft wood	32 mm
No-load speed	0 - 1100 rpm
Speed at rated load	830 rpm
Bit retainer	SDS-plus
Collar diameter	50 mm
Weight (without power cable)	3.1 kg
Cable length	4 m

Vibration

Hammer drilling concrete	12.9 m/s ²
Uncertainty of measurement K	2.4 m/s ²
Chiseling	8.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	89 dB(A)
Sound power level (LwA)	99 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Keyless chuck for tools with cylindrical shank
 rubber-coated side handle
 Drilling depth guide
 metaBOX 145 L