

TS 254 (600668380) Table saw (220-240 V / 50 - 60 Hz); Cardboard box; with stand and trolley function

Order no. 600668380
EAN 4007430214195



Product may differ from Image



- Extremely light table saw with trolley function for more mobility on the construction site
- Integrated stand made from stable die-cast aluminium (patented): unfolded in a matter of seconds with secure stand
- Very compact with folded stand for comfortable transport and space-saving storage
- Second working height for working near ground level
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precise parallel guide/rip fence with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 – 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be lowered without tools for hidden cuts and transport
- Precise, extendable table width extension for extra large working surfaces

Technical data

Characteristics

Dimensions	740 x 750 x 355 mm
Max. support surface	970 x 995 mm
Working height	850 / 355 mm
Cutting height	0 - 87 mm
Maximum cutting height 90/45°	87 / 54 mm
Maximum cutting width at rip fence	630 mm
Maximum material width at mitre fence	200 mm
No-load speed	4200 rpm
Cutting speed	56 m/s
Saw blade	254 x 30 mm
Saw blade swivel range	-1.5 - 46.5 °
Mains voltage	220 - 240 V
Rated input power	2000 W
Rated input power S1 100%	1700 W
Rated input power S6 20%	2000 W
Weight	33.4 kg
Cable length	3.1 m

Noise emission

Sound pressure level	99 dB(A)
Sound power level (LwA)	112 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (40 teeth)

Stand

Hard rubber tyres

Rip Fence

Mitre Fence

Table Length Extension

Table width extension (right)

Saw blade case

Push stick