

TPS 16000 S Combi (0251600000) Combi submersible pump (220-240 V / 50 Hz); Cardboard box

Order no. 0251600000

EAN 4003665502335



Product may differ from Image



- Multi-functional use as submersible pump for fresh water or dirty water
- For pumping empty, pumping dry and circulating fresh water and dirty water from containers, tanks or flooded cellars
- Low-intake up to 1 mm in clear water mode
- Simple and comfortable adjustment of the pump base for the required function
- Double seal system for protection of the pump if the water is particularly dense or contains large particles
- Overload protection: protects the motor from overheating
- Adjustable float switch for automatic mode
- Easy switching over from automatic mode with float switch to manual mode for low-intake suction
- Housing made of impact-proof plastic
- As dirty water submersible pump suitable for coarse fluids with a particle size of up to 30 mm
- Ergonomic handle for comfortable transport

Technical data

Characteristics

| | |
|-----------------------------|----------------------|
| Rated input power | 970 W |
| Maximum delivery rate | 16000 l/h |
| Maximum delivery height | 9.5 m |
| Maximum pressure | 0.95 bar |
| Maximum immersion depth | 7 m |
| Discharge port | 1 1/2" female thread |
| Pump housing | Plastic |
| Protection type IP | IP X8 |
| Maximum particle size up to | 30 mm |
| Number of impellers | 1 |
| Dimensions | 245 x 179 x 360 mm |
| Weight | 7.8 kg |
| Cable length | 10 m |

Scope of delivery

Angle connection piece with multi-adapter
Float switch