

WE 15-125 Quick (600448390) Angle grinder (110-120 V / 50 - 60 Hz); Cardboard box

Order no. 600448390 EAN 4007430245519



Product may differ from Image



- Highest service life for extreme applications: robust, powerful angle grinder with maximum power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

Disc-Ø	125 mm
Rated input power	1550 W
Output power	900 W
No-load speed	11000 rpm
Speed at rated load	11000 rpm
Torque	3.5 Nm
Spindle thread	M 14
Handle circumference	206 mm
Weight (without power cable)	2.5 kg
Cable length	4 m
Vibration	
Surface grinding	6 m/s²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	3.6 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	93 dB(A)
Sound pressure level Sound power level (LwA)	93 dB(A) 104 dB(A)

Scope of delivery

Guard Inner support flange M-Quick flange nut Metabo VibraTech (MVT) side handle