

## KHE 3251 (600659000) Combination hammer

(220-240 V / 50 - 60 Hz); metaBOX 165 L; with Metabo Quick change chuck

Order no. 600659000

EAN 4007430208705



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Ergonomic housing shape for chiselling tasks without side handle
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Cable-protecting ball joint for optimal freedom of motion when working
- With metaBOX, the intelligent solution for transport and storage

## Technical data

### Characteristics

|                                     |              |
|-------------------------------------|--------------|
| Max. single blow energy (EPTA)      | 3.1 J        |
| Maximum impact rate                 | 4470 bpm     |
| Rated input power                   | 800 W        |
| Drill-Ø concrete with hammer drills | 32 mm        |
| Drill-Ø masonry with core bits      | 82 mm        |
| Drill Ø steel                       | 13 mm        |
| Drill-Ø soft wood                   | 35 mm        |
| No-load speed                       | 0 - 1150 rpm |
| Speed at rated load                 | 920 rpm      |
| Bit retainer                        | SDS-plus     |
| Collar diameter                     | 50 mm        |
| Weight (without power cable)        | 3.6 kg       |
| Cable length                        | 4 m          |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 12.9 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Chiseling                    | 10.9 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 91 dB(A)  |
| Sound power level (LwA)      | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end  
 Keyless chuck for tools with cylindrical shank  
 Metabo VibraTech (MVT) side handle  
 Drilling depth guide  
 metaBOX 165 L