

TS 254 (600668380) Table saw (220-240 V / 50 - 60 Hz); Cardboard box; with stand and trolley function

Order no. 600668380
EAN 4007430214195



Product may differ from Image



- Extremely light table saw with trolley function for more mobility on the construction site
- Integrated stand made from stable die-cast aluminium (patented): unfolded in a matter of seconds with secure stand
- Very compact with folded stand for comfortable transport and space-saving storage
- Second working height for working near ground level
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precise parallel guide/rip fence with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 – 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be lowered without tools for hidden cuts and transport
- Precise, extendable table width extension for extra large working surfaces

Technical data

Characteristics

| | |
|---------------------------------------|--------------------|
| Dimensions | 740 x 750 x 355 mm |
| Max. support surface | 970 x 995 mm |
| Working height | 850 / 355 mm |
| Cutting height | 0 - 87 mm |
| Maximum cutting height 90/45° | 87 / 54 mm |
| Maximum cutting width at rip fence | 630 mm |
| Maximum material width at mitre fence | 200 mm |
| No-load speed | 4200 rpm |
| Cutting speed | 56 m/s |
| Saw blade | 254 x 30 mm |
| Saw blade swivel range | -1.5 - 46.5 ° |
| Mains voltage | 220 - 240 V |
| Rated input power | 2000 W |
| Rated input power S1 100% | 1700 W |
| Rated input power S6 20% | 2000 W |
| Weight | 33.4 kg |
| Cable length | 3.1 m |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 99 dB(A) |
| Sound power level (LwA) | 112 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (40 teeth)
 Stand
 Hard rubber tyres
 Rip Fence
 Mitre Fence
 Table Length Extension
 Table width extension (right)
 Saw blade case
 Push stick