

## Power 180-5 W OF (601531000) Compressor (230 V / 50 Hz); Cardboard box

Order no. 601531000 EAN 4007430244406



Product may differ from Image



- Compact and mobile piston compressor for flexible use both indoors and on construction sites
- Portable assembly compressor ideal for tackers and nails as well as for splitting pipes
- For single phase alternating current
- Oil-free piston compressor: simple transportation and reduced service requirements
- Instrument panel with easy to read manometer for tank- and working pressure
- Operating pressure can be regulated according to application by means of a pressure reducer and manometer
- Fittings and control elements protected in tubular frames and clearly visible
- Cable winding mechanism
- Convenient pressure switch for good cold starting, complete with relief valve
- Overload protection: protects the motor from overheating
- Rubberised feet for optimum stability

www.metabo.com 1/2



Technical data	
Characteristics	
Suction rate	160 l/min
Filling capacity	90 l/min
Effective delivery volume (at 80% max. pressure)	75 l/min
Maximum pressure	8 bar
Rated input power	1.1 kW
Maximum speed	2850 rpm
Tank capacity	51
Sound pressure level (LpA)	82 dB(A)
Sound power level (LwA)	96 dB(A)
Dimensions	370 x 395 x 286 mm
Weight	16 kg
Cable length	2.4 m
Noise emission	
Sound pressure level	82 dB(A)
Sound power level (LwA)	96 dB(A)

## Scope of delivery

Universal quick-action coupling

www.metabo.com 2/2