

## **KH 18 LTX 24 (601712840) Cordless hammer** **18V; metaBOX 165 L**

Order no. 601712840  
EAN 4061792218239



Product may differ from Image



- Cordless hammer with SDS plus holder for powerful hammer drilling and chiselling - any time and anywhere
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Variospeed (V) Electronics for working at customised speeds to suit various application materials
- Electronic soft start for precise spot-drilling
- Safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- With attachment point for tool safety straps for working at great heights
- LED work light for optimum view of the drilling site
- Dust-free drilling with external dust extraction ESA plus (accessory)
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                                     |              |
|-------------------------------------|--------------|
| Battery voltage                     | 18 V         |
| Max. single blow energy (EPTA)      | 2.1 J        |
| Maximum impact rate                 | 5200 bpm     |
| Drill-Ø concrete with hammer drills | 24 mm        |
| Drill-Ø masonry with core bits      | 68 mm        |
| Drill Ø steel                       | 13 mm        |
| Drill-Ø soft wood                   | 30 mm        |
| No-load speed                       | 0 - 1400 rpm |
| Bit retainer                        | SDS-plus     |
| Weight without battery pack         | 2.6 kg       |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 11.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Chiseling                    | 7.8 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 91 dB(A) |
| Sound power level (LwA)      | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Side handle  
 Drilling depth guide  
 metaBOX 165 L  
 without battery pack, without charger