

PFM 17 (601789500) Metal weld bead remover (220-240 V / 50 - 60 Hz); metaBOX 280 L

Order no. 601789500 EAN 4061792210349



Product may differ from Image











- Fast, clean removal of weld beads in one work step with the newly developed metal weld bead remover
- Small metal chips are generated during face milling (no metal dust that is a health hazard)
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1mm steps.
- Ready for use in a matter of seconds thanks to fixable, magnetic guide rail (50 cm long, expandable).
- Simple, comfortable change of the indexable inserts at the milling head
- Slim handle area and large bow-type handle that can be adjusted without tools for safe, uniform guidance
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start and restart protection
- With metaBOX, the intelligent solution for transport and storage

www.metabo.com 1/2



Technical data		
Characteristics		
No-load speed	8000 - 12600 rpm	
Rated input power	1700 W	
Output power	970 W	
Removal width	25 mm	
Removal height	- 1.5 - 10 mm	
Grading of cutting depth setting	0.1 mm	
Weight (without power cable)	4.6 kg	
Cable length	3.6 m	
Vibration		
Vibration	4.1 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	91 dB(A)	
Sound power level (LwA)	102 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Magnetic guide rail (50 cm long)
3 Carbide indexable inserts Universal
Bow-type handle
Screwdriver for Torx screws 15
Screwdriver SW 4 with T-handle
Open-jawed spanner SW 10
metaBOX 280 L

www.metabo.com 2 / 2