

## WEF 9-125 Quick (613060390) Flat-head angle grinder (110-120 V / 50 - 60 Hz); Cardboard box

Order no. 613060390 EAN 4007430243683



Product may differ from Image



- Most compact flat-head angle grinder for working at acute angles down to 43°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Metabo Marathon motor with patented dust protection for long service life
- Constamatic (C)-Full wave electronics: fast work progress by means of almost constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Electronic overload protection, soft start and restart protection
- Auto-stop carbon brushes to protect the motor

## Technical data

## Characteristics

| Minimum accessible angle     | 43 °                 |
|------------------------------|----------------------|
| Disc-Ø                       | 125 mm               |
| Rated input power            | 910 W                |
| Output power                 | 430 W                |
| No-load speed                | 10000 rpm            |
| Speed at rated load          | 8200 rpm             |
| Torque                       | 2 Nm                 |
| Spindle thread               | M 14                 |
| Weight (without power cable) | 2.1 kg               |
| Cable length                 | 4 m                  |
| Handle circumference         | 197 mm               |
| Vibration                    |                      |
| Surface grinding             | 5.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s²             |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s²             |
| Noise emission               |                      |
| Sound pressure level         | 88 dB(A)             |
| Sound power level (LwA)      | 99 dB(A)             |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard Inner support flange Quick-locking nut Side handle 1 Flap disc Flexiamant Super Convex (125mm; P60)