

## WEV 15-125 Quick (600468420) Angle Grinder Cardboard box; with speed control, quick-locking nut

Order no. 600468420 EAN 4007430243898



Representative picture


















- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values	
Parameters	
Amps	13.5 AMPS
Disc diameter	5 "
Output power	900 W
No-load speed	2800 - 11000 RPM
Speed at rated load	11000 RPM
Torque	31 in-lbs
Spindle thread	5/8" - 11 UNC
Grip circumference	8 1/8 "
Weight (without power cable)	5.5 lbs
Cable length	8 ft
Vibration	
Surface grinding	6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	3.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle Metabo VibraTech (MVT)

www.metabo.com 2/2