

WEV 17-125 Quick Inox (600517420) Angle Grinder Cardboard box; with speed control, quick-locking nut

Order no. 600517420 EAN 4061792176249



Representative picture















- Perfect processing of stainless steel: robust, powerful angle grinder with high gear reduction and highly reduced, adjustable speed for cool finish
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



| Technical values | | |
|------------------------------|----------------------|--|
| Parameters | | |
| Amps | 14.5 AMPS | |
| Disc diameter | 5 " | |
| Rated input power | 1700 W | |
| Output power | 1040 W | |
| No-load speed | 2000 - 7600 RPM | |
| Speed at rated load | 7600 RPM | |
| Torque | 44 in-lbs | |
| Spindle thread | 5/8" - 11 UNC | |
| Grip circumference | 8 1/8 " | |
| Weight (without power cable) | 5.5 lbs | |
| Cable length | 8 ft | |
| Vibration | | |
| Surface grinding | 4.7 m/s² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Polishing | 2.5 m/s ² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Grinding with sandpaper | 2.5 m/s ² | |
| Uncertainty of measurement K | 1.5 m/s² | |
| Noise emission | | |
| Sound pressure level | 93 dB(A) | |
| Sound power level (LwA) | 104 dB(A) | |
| Uncertainty of measurement K | 3 dB(A) | |

Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle Metabo VibraTech (MVT)

www.metabo.com 2/2