

WEPBA 17-125 Quick RT DS (600605420) Angle Grinder Cardboard box

Order no. 600605420 EAN 4007430320278



Representative picture























- Maximum productivity through strong power at a low weight
- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Perfect ergonomics thanks to a slim grip area for maximum control and easily working overhead
- · Metabo LongLife Motor with new cooling and carbon brush system for double the service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for disc change without tools at the push of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibration for fatigue-free work with Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Highest user safety with patented, mechanical disc brake and deadman switch: disc stops in 2 seconds after release, even during a power failure
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Electronic soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values	
Parameters	
Amps	14.5 AMPS
Disc diameter	5 "
Output power	1000 W
No-load speed	10000 RPM
Speed at rated load	10000 RPM
Torque	34 in-lbs
Spindle thread	5/8" - 11 UNC
Grip circumference	5.438 "
Weight (without power cable)	6 lbs
Cable length	8 ft
Vibration	
Surface grinding	6.1 m/s ²
Uncertainty of measurement K	1.5 m/s²
Grinding with sandpaper	4.4 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle Metabo VibraTech (MVT)

www.metabo.com 2/2