

KHA 18 LTX BL 40 (600752840) Cordless Hammer 18V; Plastic Carry Case

Order no. 600752840
EAN 4061792199934



Representative picture



- Cordless hammer with SDS-max mount for extremely powerful hammer drilling and chiseling - anytime and anywhere
- Maximum drilling power, efficiency, and service life with brushless technology and high-performance hammer action
- Combination hammer with 2 functions: hammer drilling, drilling, and chiseling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- High performance hammer action, precisely mounted in a housing made of aluminum alloy: long-lasting and robust
- Vario Tacho Constamatic (VTC) Electronics-Full wave electronics for drilling at customized speeds to suit the application materials, and speeds that remain almost constant even under load
- Optional speed and impact energy reduction for drilling and working on softer materials
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly.
- With attachment point for tool safety belt for working at heights
- LED work light for optimal view of the drilling site
- Low-dust chiseling and drilling with external ESA max dust extraction (accessories)
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: www.cordless-alliance-system.com

Technical values

Parameters

Battery voltage	18 V
Max. single blow energy (EPTA)	8.6 J
Maximum impact rate	3200 BPM
Max. capacity in concrete with hammer drills	1 9/16 "
Max. capacity in masonry with core bits	4 1/8 "
No-load speed	450 - 580 RPM
Bit retainer	SDS-max
Weight without battery pack	15.3 lbs
Weight including battery pack	17.5 lbs

Vibration

Hammer drilling concrete	12.5 m/s ²
Uncertainty of measurement K	4.2 m/s ²
Chiseling	8.5 m/s ²
Uncertainty of measurement K	3.2 m/s ²

Noise emission

Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

rubber-coated handle
 Side Handle
 Drilling depth guide
 Lubricant for tool shank end
 Duster
 Plastic carrying case
 without battery pack, without charger