

## KH 18 LTX BL 28 Q (601715840) Cordless Hammer 18V; metaBOX 165 L; with Metabo Quick Chuck

Order no. 601715840 EAN 4061792218611



Representative picture

















- Extremely lightweight and easy to handle cordless hammer with integrated suction interface
- Maximum drilling power, efficiency, and service life with brushless technology and high-performance hammer acttion
- Dust-free drilling with compact dust extraction ISA 28 (accessory)
- Combination hammer with 3 functions: hammer drilling, drilling, and chiseling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- · Metabo Quick: Quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- · Optional speed and impact energy reduction for drilling and working on softer materials
- Electronic soft start for precise spot-drilling
- Twice as safe during drill bit blocking: no kick-back, thanks to mechanical decoupling, plus lightning-fast, sensor-controlled shut-down
- LED work light for optimal view of the drilling site
- Multiple brands, one battery pack system: This product can be used with all 18 V battery packs and chargers from CAS brands: www.cordless-alliance-system.com

www.metabo.com 1/2



Technical values	
Parameters	
Battery voltage	18 V
Max. single blow energy (EPTA)	3 J
Maximum impact rate	4470 BPM
Max. capacity in concrete with hammer drills	1 3/32 "
Max. capacity in masonry with core bits	3 7/32 "
Max. capacity in steel	1/2 "
Max. capacity in soft wood	1 3/16 "
No-load speed	0 - 1000 RPM
Bit retainer	SDS-plus
Weight without battery pack	7.5 lbs
Vibration	
Hammer drilling concrete	18.2 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Chiseling	13.4 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Hammer chuck for tools with SDS-plus shank end Keyless chuck for tools with cylindrical shank end rubber-coated handle Drilling depth guide metaBOX 165 L without battery pack, without charger

www.metabo.com 2/2